

Package ‘WBI’

March 11, 2026

Type Package

Title Wasserstein Bipolarization Index

Version 0.1.0

Description Computation of the Wasserstein Bipolarization Index as described in Lee and Sobel (Forthcoming) [doi:10.48550/arXiv.2408.03331](https://doi.org/10.48550/arXiv.2408.03331). Provides both asymptotic (Sommerfeld, 2017 <https://ediss.uni-goettingen.de/bitstream/handle/11858/00-1735-0000-0023-3FA1-C/DissertationSommerfeldRev.pdf?sequence=1>) and bootstrap methods (Efron and Narasimhan, 2020 [doi:10.1080/10618600.2020.1714633](https://doi.org/10.1080/10618600.2020.1714633)) for calculating confidence intervals.

License MIT + file LICENSE

Encoding UTF-8

Imports transport, dplyr, bcaboot

RoxygenNote 7.3.3

Suggests spelling

Language en-US

NeedsCompilation no

Author Hane Lee [aut, cre]

Maintainer Hane Lee <h13333@columbia.edu>

Repository CRAN

Date/Publication 2026-03-11 16:40:11 UTC

Contents

WBI	2
WBI_boot	3
Index	4

WBI*Wasserstein Bipolarization Index*

Description

This function takes a vector of observed responses and computes the Wasserstein Bipolarization Index and its asymptotic confidence interval with the maximum polarization distribution (with 0.5 masses each on min and max) as the maximally separated measure.

Usage

```
WBI(obs, wp, min, max, alpha, wt = rep(c(1/length(obs)), length(obs)))
```

Arguments

<code>obs</code>	A vector of observed responses.
<code>wp</code>	The order (p) of the p -Wasserstein distance. Use $p=1$ to only account for spread, $p>1$ to account for spread and bi-clustering.
<code>min</code>	The minimum of the response scale.
<code>max</code>	The maximum of the response scale.
<code>alpha</code>	Significance level of the confidence interval.
<code>wt</code>	Weight of each observation, with default set to uniform.

Value

A vector of length three containing the CI lower bound, point estimate, and CI upper bound.

Examples

```
# We want to measure WBI of an opinion item measured on [0,100].
# We choose W2 distance and 95% asymptotic confidence intervals.
data <- c(20, 100, 50, 50, 0,
          90, 85, 10, 25, 10,
          30, 90, 80, 0, 100,
          20, 30, 0, 65, 95)
results <- WBI(data, 2, 0, 100, 0.05)
```

WBI_boot*Wasserstein Bipolarization Index with Bootstrap Confidence Intervals*

Description

This function takes a vector of observed responses and computes the Wasserstein Bipolarization Index and its bootstrap confidence interval with the maximum polarization distribution (with 0.5 masses each on min and max) as the maximally separated measure. We use the package `bcaboot` for bootstrap.

Usage

```
WBI_boot(obs, wp, min, max, alpha, r = 5000)
```

Arguments

<code>obs</code>	A vector of observed responses.
<code>wp</code>	The order (p) of the p -Wasserstein distance. Use $p=1$ to only account for spread, $p>1$ to account for spread and bi-clustering.
<code>min</code>	The minimum of the response scale.
<code>max</code>	The maximum of the response scale.
<code>alpha</code>	Significance level of the confidence interval.
<code>r</code>	Number of Bootstrap replications

Value

A vector of length three containing the CI lower bound, point estimate, and CI upper bound.

Examples

```
# We want to measure WBI of an opinion item measured on [0,100].
# We choose W2 distance and 95% bootstrap confidence intervals.
# r=1 for automatic testing (runs quickly)
data <- c(20, 100, 50, 50, 0,
          90, 85, 10, 25, 10,
          30, 90, 80, 0, 100,
          20, 30, 0, 65, 95)
results <- WBI_boot(data, 2, 0, 100, 0.05, r=1)
```

Index

WBI, [2](#)

WBI_boot, [3](#)