

Package ‘chmsflow’

June 8, 2026

Type Package

Title Transforming and Harmonizing CHMS Variables

Version 0.1.0

Description Harmonizes variables from the Canadian Health Measures Survey (CHMS) across cycles 1-6 (2007-2019), producing consistent, analysis-ready variables for use with CHMS data. Recoding is data-driven through metadata tables and applied with `recodeflow::rec_with_table()` from the 'recodeflow' package. The recoding approach builds on `sjmisc::rec()` from the 'sjmisc' package (Ludecke 2018) <[doi:10.21105/joss.00754](https://doi.org/10.21105/joss.00754)>.

Depends R (>= 4.1.0)

Imports dplyr, haven, purrr, recodeflow

License MIT + file LICENSE

URL <https://github.com/Big-Life-Lab/chmsflow>,
<https://big-life-lab.github.io/chmsflow/>

BugReports <https://github.com/Big-Life-Lab/chmsflow/issues>

Encoding UTF-8

RoxygenNote 7.3.3

Suggests DT, kableExtra, knitr, quarto, readr, testthat (>= 3.0.0)

VignetteBuilder quarto

Config/build/clean-inst-doc FALSE

LazyData true

NeedsCompilation no

Author Rafidul Islam [aut, cre, cph] (ORCID:
<<https://orcid.org/0009-0008-3072-5623>>),
Douglas Manuel [aut, cph] (ORCID:
<<https://orcid.org/0000-0003-0912-0845>>),
Therese Chan [ctb] (ORCID: <<https://orcid.org/0009-0002-2291-7218>>),
The Ottawa Hospital Research Institute [cph]

Maintainer Rafidul Islam <raislam@ohri.ca>

Repository CRAN

Date/Publication 2026-06-08 18:00:08 UTC

Contents

adjust_dbp	3
adjust_sbp	4
aggregate_meds_by_person	5
calculate_exercise_daily_avg	6
calculate_exercise_weekly	8
calculate_fv_daily_cycles1to2	9
calculate_fv_daily_cycles3to6	11
calculate_gfr	14
calculate_household_income	15
calculate_nonhdl	17
calculate_pack_years	18
calculate_waist_height_ratio	20
categorize_ckd	22
categorize_diet_quality	23
categorize_exercise	25
categorize_income_quintile	26
categorize_nonhdl	27
cycle1	29
cycle1_meds	29
cycle2	30
cycle2_meds	30
cycle3	31
cycle3_meds	31
cycle4	32
cycle4_meds	32
cycle5	33
cycle5_meds	33
cycle6	34
cycle6_meds	34
derive_alcohol_risk	35
derive_alcohol_risk_detailed	37
derive_cvd_family_history	39
derive_cvd_personal_history	41
derive_diabetes_status	42
derive_hypertension	44
derive_hypertension_adj	47
derive_hypertension_control	49
derive_hypertension_control_adj	52
is_ace_inhibitor	54
is_ace_med_cycles1to2	55
is_any_antihtn_med	61
is_any_htn_med_cycles1to2	62
is_bb_med_cycles1to2	67
is_beta_blocker	73
is_calcium_channel_blocker	74
is_ccb_med_cycles1to2	75

is_diabetes_med	81
is_diab_med_cycles1to2	82
is_diuretic	87
is_diur_med_cycles1to2	88
is_lowest_income_quintile	94
is_misc_htn_med_cycles1to2	95
is_nsaid	100
is_nsaid_med_cycles1to2	101
is_other_antihtn_med	107
recode_after_meds	108
recode_meds_cycles1to2	109
recode_meds_cycles3to6	110
variables	111
variable_details	112

Index**113**

adjust_dbp	<i>Adjusted diastolic blood pressure</i>
------------	--

Description

This function adjusts diastolic blood pressure based on the respondent's diastolic average blood pressure across six measurements. The adjustment is made using specific correction factors. The adjusted diastolic blood pressure is returned as a numeric value.

Usage

```
adjust_dbp(bpmdpbbpd)
```

Arguments

bpmdpbbpd	numeric A numeric representing the respondent's diastolic average blood pressure (in mmHg) across six measurements.
-----------	--

Details

Blood pressure measurements in survey settings may require adjustment to account for measurement conditions and equipment differences. This function applies a standardized adjustment using the formula: $dbp_adj_mmhg = 15.6 + (0.83 * bpmdpbbpd)$.

****Missing Data Codes:****

- `996`: Valid skip (e.g., measurement not taken). Handled as `haven::tagged_na("a")`.
- `997-999`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.

Value

numeric The adjusted diastolic blood pressure as a numeric.

See Also

[adjust_sbp\(\)](#) for systolic blood pressure adjustment, [derive_hypertension\(\)](#) for hypertension classification

Examples

```
# Scalar usage: Single respondent
# Example: Adjust for a respondent with average diastolic blood pressure of 80 mmHg.
adjust_dbp(bpmdpbbpd = 80)
# Output: 82

# Example: Adjust for a respondent with a non-response diastolic blood pressure of 996.
result <- adjust_dbp(bpmdpbbpd = 996)
result # Shows: NA
haven::is_tagged_na(result, "a") # Shows: TRUE (confirms it's tagged NA(a))
format(result, tag = TRUE) # Shows: "NA(a)" (displays the tag)

# Multiple respondents
adjust_dbp(bpmdpbbpd = c(80, 90, 100))
# Returns: c(82, 90.3, 98.6)

# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(dbp_adj_mmhg = adjust_dbp(bpmdpbbpd)) |>
  head()
```

adjust_sbp

Adjusted systolic blood pressure

Description

This function adjusts systolic blood pressure based on the respondent's systolic average blood pressure across six measurements. The adjustment is made using specific correction factors. The adjusted systolic blood pressure is returned as a numeric value.

Usage

```
adjust_sbp(bpmdpbbps)
```

Arguments

bpmdpbbps **numeric** A numeric representing the respondent's systolic average blood pressure (in mmHg) across six measurements.

Details

Blood pressure measurements in survey settings may require adjustment to account for measurement conditions and equipment differences. This function applies a standardized adjustment using the formula: $sbp_adj_mmhg = 11.4 + (0.93 * bpmdpbps)$.

```

**Missing Data Codes:**
- `996`: Valid skip (e.g., measurement not taken). Handled as `haven::tagged_na("a")`.
- `997-999`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.

```

Value

numeric The adjusted systolic blood pressure as a numeric.

See Also

[adjust_dbp\(\)](#) for diastolic blood pressure adjustment, [derive_hypertension\(\)](#) for hypertension classification

Examples

```

# Scalar usage: Single respondent
# Example: Adjust for a respondent with average systolic blood pressure of 120 mmHg.
adjust_sbp(bpmdpbps = 120)
# Output: 123

# Example: Adjust for a respondent with a non-response systolic blood pressure of 996.
result <- adjust_sbp(bpmdpbps = 996)
result # Shows: NA
haven::is_tagged_na(result, "a") # Shows: TRUE (confirms it's tagged NA(a))
format(result, tag = TRUE) # Shows: "NA(a)" (displays the tag)

# Multiple respondents
adjust_sbp(bpmdpbps = c(120, 130, 140))
# Returns: c(123, 132.3, 141.6)

# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(sbp_adj_mmhg = adjust_sbp(bpmdpbps)) |>
  head()

```

Description

Collapses long-format medication data (cycles 3-6) to one row per respondent by taking the maximum value of each medication variable across all rows. A result of 1 (taking the medication) takes precedence over 0. Tagged NAs are propagated only when all rows for a respondent are missing.

Usage

```
aggregate_meds_by_person(data, variables, by = "clinicid")
```

Arguments

`data` [data.frame](#) Long-format medication data with multiple rows per respondent.
`variables` [character](#) Variable names to aggregate.
`by` [character](#) The respondent identifier column. Default is "clinicid".

Value

[data.frame](#) One row per respondent with aggregated medication variables as numeric.

See Also

[recode_meds_cycles3to6\(\)](#), [recode_meds_cycles1to2\(\)](#)

Examples

```
df <- data.frame(
  clinicid = c(1, 1, 2, 2),
  any_htn_med = c(0, 1, 0, 0),
  diab_med = c(1, 0, 0, 0)
)
aggregate_meds_by_person(df, variables = c("any_htn_med", "diab_med"))
```

calculate_exercise_daily_avg

Average daily minutes of moderate-to-vigorous physical activity (MVPA) from accelerometer data

Description

This function calculates the average daily minutes of moderate-to-vigorous physical activity (MVPA) across a week of accelerometer measurement. It takes seven parameters, each representing the MVPA minutes on a specific day (Day 1 to Day 7). The function computes the daily average across the week.

Usage

```
calculate_exercise_daily_avg(  
  ammdmva1,  
  ammdmva2,  
  ammdmva3,  
  ammdmva4,  
  ammdmva5,  
  ammdmva6,  
  ammdmva7  
)
```

Arguments

ammdmva1	numeric A numeric representing minutes of moderate-to-vigorous physical activity (MVPA) on Day 1 of accelerometer measurement.
ammdmva2	numeric A numeric representing minutes of MVPA on Day 2 of accelerometer measurement.
ammdmva3	numeric A numeric representing minutes of MVPA on Day 3 of accelerometer measurement.
ammdmva4	numeric A numeric representing minutes of MVPA on Day 4 of accelerometer measurement.
ammdmva5	numeric A numeric representing minutes of MVPA on Day 5 of accelerometer measurement.
ammdmva6	numeric A numeric representing minutes of MVPA on Day 6 of accelerometer measurement.
ammdmva7	numeric A numeric representing minutes of MVPA on Day 7 of accelerometer measurement.

Details

This function processes physical activity data from accelerometer measurements to create a weekly activity summary.

****Data Quality Requirements:****

- Requires complete 7-day data (missing days result in tagged NA)
- This conservative approach ensures reliable activity estimates
- Zero values are preserved (represent valid no-activity days)

****Missing Data Codes:****

- For all input variables:
 - `9996`: Valid skip. Handled as `haven::tagged_na("a")`.
 - `9997-9999`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.

Value

numeric The average daily minutes of MVPA across a week of accelerometer use. If inputs are invalid or out of bounds, the function returns a tagged NA.

See Also

[calculate_exercise_weekly\(\)](#) for activity unit conversion, [categorize_exercise\(\)](#) for activity level classification

Examples

```
# Scalar usage: Single respondent
# Example: Calculate the average minutes of exercise per day for a week of accelerometer data.
calculate_exercise_daily_avg(30, 40, 25, 35, 20, 45, 50)
# Output: 35

# Example: Respondent has non-response values for all inputs.
result <- calculate_exercise_daily_avg(9998, 9998, 9998, 9998, 9998, 9998, 9998)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

# Multiple respondents
calculate_exercise_daily_avg(
  c(30, 20), c(40, 30), c(25, 35), c(35, 45),
  c(20, 25), c(45, 55), c(50, 60)
)
# Returns: c(35, 39.28571)

# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(avg_exercise = calculate_exercise_daily_avg(ammdmva1, ammdmva2,
    ammdmva3, ammdmva4, ammdmva5, ammdmva6, ammdmva7)) |>
  head()
```

calculate_exercise_weekly

*Weekly minutes of moderate-to-vigorous physical activity (MVPA)
from daily average*

Description

This function takes the average daily minutes of moderate-to-vigorous physical activity (MVPA) across a week of accelerometer use as an input (`mvpa_min`) and calculates the equivalent weekly MVPA minutes. The result is returned as a numeric value.

Usage

```
calculate_exercise_weekly(mvpa_min)
```

Arguments

`mvpa_min` **numeric** A numeric representing the average daily minutes of moderate-to-vigorous physical activity (MVPA) across a week of accelerometer use.

Details

The function multiplies the average daily MVPA minutes (`mvpa_min`) by 7 to obtain the equivalent weekly MVPA minutes.

```
**Missing Data Codes:**  
- Propagates tagged NAs from the input `mvpa_min`.
```

Value

numeric The total weekly minutes of MVPA. If inputs are invalid or out of bounds, the function returns a tagged NA.

See Also

[calculate_exercise_daily_avg\(\)](#), [categorize_exercise\(\)](#)

Examples

```
# Scalar usage: Single respondent  
# Example: Convert average daily MVPA minutes to weekly MVPA minutes.  
calculate_exercise_weekly(35)  
# Output: 245  
  
# Multiple respondents  
calculate_exercise_weekly(c(35, 40, 20))  
# Returns: c(245, 280, 140)  
  
# Database usage: Applied to survey datasets  
library(dplyr)  
cycle4 |>  
  mutate(avg_exercise = calculate_exercise_daily_avg(ammdmva1, ammdmva2,  
    ammdmva3, ammdmva4, ammdmva5, ammdmva6, ammdmva7)) |>  
  mutate(min_per_week = calculate_exercise_weekly(avg_exercise)) |>  
  head()
```

Description

This function calculates the daily fruit and vegetable consumption in a year for respondent in the Canadian Health Measures Survey (CHMS) cycles 1-2. It takes seven parameters, each representing the number of times per year a specific fruit or vegetable item was consumed. The function then sums up the consumption frequencies of all these items and divides the total by 365 to obtain the average daily consumption of fruits and vegetables in a year.

Usage

```
calculate_fv_daily_cycles1to2(
  wsdd14y,
  gfvd17y,
  gfvd18y,
  gfvd19y,
  gfvd20y,
  gfvd22y,
  gfvd23y
)
```

Arguments

wsdd14y	numeric A numeric vector representing the number of times per year fruit juice was consumed.
gfvd17y	numeric A numeric vector representing the number of times per year fruit (excluding juice) was consumed.
gfvd18y	numeric A numeric vector representing the number of times per year tomato or tomato sauce was consumed.
gfvd19y	numeric A numeric vector representing the number of times per year lettuce or green leafy salad was consumed.
gfvd20y	numeric A numeric vector representing the number of times per year spinach, mustard greens, and cabbage were consumed.
gfvd22y	numeric A numeric vector representing the number of times per year potatoes were consumed.
gfvd23y	numeric A numeric vector representing the number of times per year other vegetables were consumed.

Details

The function calculates the total consumption of fruits and vegetables in a year by summing up the consumption frequencies of all the input items. It then divides the total by 365 to obtain the average daily consumption of fruits and vegetables in a year.

```
**Missing Data Codes:**
- For all input variables:
  - `9996`: Valid skip. Handled as `haven::tagged_na("a")`.
  - `9997-9999`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.
```

Value

numeric The average times per day fruits and vegetables were consumed in a year. If inputs are invalid or out of bounds, the function returns a tagged NA.

See Also

[calculate_fv_daily_cycles3to6\(\)](#) for cycles 3-6 fruit and vegetable consumption, [categorize_diet_quality\(\)](#) for overall diet quality

Examples

```
# Scalar usage: Single respondent
# Example: Calculate average daily fruit and vegetable consumption for a cycle 1-2 respondent.
calculate_fv_daily_cycles1to2(
  wsdd14y = 50, gfvd17y = 150, gfvd18y = 200, gfvd19y = 100, gfvd20y = 80,
  gfvd22y = 120, gfvd23y = 90
)
# Output: 2.164384

# Example: Respondent has non-response values for all inputs.
result <- calculate_fv_daily_cycles1to2(
  wsdd14y = 9998, gfvd17y = 9998, gfvd18y = 9998, gfvd19y = 9998, gfvd20y = 9998,
  gfvd22y = 9998, gfvd23y = 9998
)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

# Multiple respondents
calculate_fv_daily_cycles1to2(
  wsdd14y = c(50, 60), gfvd17y = c(150, 160), gfvd18y = c(200, 210), gfvd19y = c(100, 110),
  gfvd20y = c(80, 90), gfvd22y = c(120, 130), gfvd23y = c(90, 100)
)
# Returns: c(2.164384, 2.356164)

# Database usage: Applied to survey datasets
library(dplyr)
cycle2 |>
  mutate(total_fv = calculate_fv_daily_cycles1to2(wsdd14y, gfvd17y, gfvd18y,
    gfvd19y, gfvd20y, gfvd22y, gfvd23y)) |>
  head()
```

Description

This function calculates the daily fruit and vegetable consumption in a year for respondents in the Canadian Health Measures Survey (CHMS) cycles 3-6. It takes eleven parameters, each representing the number of times per year a specific fruit or vegetable item was consumed. The function then sums up the consumption frequencies of all these items and divides the total by 365 to obtain the average daily consumption of fruits and vegetables in a year.

Usage

```
calculate_fv_daily_cycles3to6(
  wsdd34y,
  wsdd35y,
  gfvd17ay,
  gfvd17by,
  gfvd17cy,
  gfvd17dy,
  gfvd18y,
  gfvd19y,
  gfvd20y,
  gfvd22y,
  gfvd23y
)
```

Arguments

wsdd34y	numeric A numeric vector representing the number of times per year orange or grapefruit juice was consumed.
wsdd35y	numeric A numeric vector representing the number of times per year other fruit juices were consumed.
gfvd17ay	numeric A numeric vector representing the number of times per year citrus fruits were consumed.
gfvd17by	numeric A numeric vector representing the number of times per year strawberries were consumed (in summer).
gfvd17cy	numeric A numeric vector representing the number of times per year strawberries were consumed (outside summer).
gfvd17dy	numeric A numeric vector representing the number of times per year other fruits were consumed.
gfvd18y	numeric A numeric vector representing the number of times per year tomato or tomato sauce was consumed.
gfvd19y	numeric A numeric vector representing the number of times per year lettuce or green leafy salad was consumed.
gfvd20y	numeric A numeric vector representing the number of times per year spinach, mustard greens, and cabbage were consumed.
gfvd22y	numeric A numeric vector representing the number of times per year potatoes were consumed.
gfvd23y	numeric A numeric vector representing the number of times per year other vegetables were consumed.

Details

The function calculates the total consumption of fruits and vegetables in a year by summing up the consumption frequencies of all the input items. It then divides the total by 365 to obtain the average daily consumption of fruits and vegetables in a year.

```
**Missing Data Codes:**
- For all input variables:
  - `9996`: Valid skip. Handled as `haven::tagged_na("a")`.
  - `9997-9999`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.
```

Value

numeric The average times per day fruits and vegetables were consumed in a year. If inputs are invalid or out of bounds, the function returns a tagged NA.

See Also

[calculate_fv_daily_cycles1to2\(\)](#) for cycles 1-2 fruit and vegetable consumption, [categorize_diet_quality\(\)](#) for overall diet quality

Examples

```
# Scalar usage: Single respondent
# Example: Calculate average daily fruit and vegetable consumption for a cycle 3-6 respondent
calculate_fv_daily_cycles3to6(
  wsdd34y = 50, wsdd35y = 100, gfvd17ay = 150, gfvd17by = 80, gfvd17cy = 40,
  gfvd17dy = 200, gfvd18y = 100, gfvd19y = 80, gfvd20y = 60, gfvd22y = 120, gfvd23y = 90
)
# Output: 2.931507

# Example: Respondent has non-response values for all inputs.
result <- calculate_fv_daily_cycles3to6(
  wsdd34y = 9998, wsdd35y = 9998, gfvd17ay = 9998, gfvd17by = 9998, gfvd17cy = 9998,
  gfvd17dy = 9998, gfvd18y = 9998, gfvd19y = 9998, gfvd20y = 9998, gfvd22y = 9998, gfvd23y = 9998
)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

# Multiple respondents
calculate_fv_daily_cycles3to6(
  wsdd34y = c(50, 60), wsdd35y = c(100, 110), gfvd17ay = c(150, 160), gfvd17by = c(80, 90),
  gfvd17cy = c(40, 50), gfvd17dy = c(200, 210), gfvd18y = c(100, 110), gfvd19y = c(80, 90),
  gfvd20y = c(60, 70), gfvd22y = c(120, 130), gfvd23y = c(90, 100)
)
# Returns: c(2.931507, 3.232877)

# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(total_fv = calculate_fv_daily_cycles3to6(wsdd34y, wsdd35y, gfvd17ay,
```

```
gfvd17by, gfvd17cy, gfvd17dy, gfvd18y, gfvd19y, gfvd20y, gfvd22y, gfvd23y)) |>
head()
```

calculate_gfr	<i>Estimated glomerular filtration rate (GFR)</i>
---------------	---

Description

This function calculates the estimated glomerular filtration rate (GFR) according to Finlay's formula, where serum creatine is in mg/dL. The calculation takes into account the respondent's ethnicity, sex, and age.

Usage

```
calculate_gfr(lab_bcre, pgdcgt, clc_sex, clc_age)
```

Arguments

lab_bcre	numeric Blood creatine (umol/L). It should be a numeric between 14 and 785.
pgdcgt	integer Ethnicity (13 categories). It should be an integer between 1 and 13.
clc_sex	integer Sex (Male = 1, Female = 2). It should be an integer of either 1 or 2.
clc_age	numeric Age (years). It should be a numeric between 3 and 79.

Details

This function implements the Modification of Diet in Renal Disease (MDRD) equation to estimate glomerular filtration rate, a key indicator of kidney function.

```
**Clinical Significance:**
GFR estimates are essential for:
- Chronic kidney disease (CKD) classification
- Medication dosing adjustments
- Cardiovascular risk assessment

**Formula Application:**
Base:  $GFR = 175 \times (creatinine^{-1.154}) \times (age^{-0.203})$ 
Adjustments:
- Female: x 0.742
- Black ethnicity: x 1.210

**Unit Conversion:**
Serum creatinine converted from umol/L to mg/dL (/ 88.4)

**Missing Data Codes:**
- `lab_bcre`: `9996` (Not applicable), `9997-9999` (Missing)
- `pgdcgt`: `96` (Not applicable), `97-99` (Missing)
- `clc_sex`: `6` (Not applicable), `7-9` (Missing)
- `clc_age`: `96` (Not applicable), `97-99` (Missing)
```

Value

numeric The calculated GFR. If inputs are invalid or out of bounds, the function returns a tagged NA.

See Also

[categorize_ckd\(\)](#) for CKD classification based on GFR values

Examples

```
# Scalar usage: Single respondent
# Example 1: Calculate gfr for a 45-year-old white female with serum creatine of 80 umol/L.
calculate_gfr(lab_bcre = 80, pgdcgt = 1, clc_sex = 2, clc_age = 45)
# Output: 67.27905

# Example 2: Respondent has non-response values for all inputs.
result <- calculate_gfr(lab_bcre = 9998, pgdcgt = 98, clc_sex = 8, clc_age = 98)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

# Multiple respondents
calculate_gfr(
  lab_bcre = c(80, 70, 90), pgdcgt = c(1, 2, 1),
  clc_sex = c(2, 2, 1), clc_age = c(45, 35, 50)
)
# Returns: c(67.27905, 99.94114, 70.38001)

# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(gfr = calculate_gfr(lab_bcre, pgdcgt, clc_sex, clc_age)) |>
  head()
```

calculate_household_income

Adjusted total household income

Description

This function calculates the adjusted total household income based on the respondent's income amount and actual household size, taking into account the weighted household size.

Usage

```
calculate_household_income(thi_01, dhhhsz)
```

Arguments

thi_01	numeric A numeric representing the respondent's household income amount in dollars.
dhhdsz	integer An integer representing the respondent's actual household size in persons.

Details

This function applies equivalence scales to adjust household income for household size, allowing for meaningful income comparisons across different household compositions.

```

**Equivalence Scale Logic:**
- First adult: Weight = 1.0 (full weight)
- Second adult: Weight = 0.4 (economies of scale)
- Additional members: Weight = 0.3 each (further economies)

**Missing Data Codes:**
- `thi_01`:
  - `99999996`: Valid skip. Handled as `haven::tagged_na("a")`.
  - `99999997-99999999`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.
- `dhhdsz`:
  - `96`: Valid skip. Handled as `haven::tagged_na("a")`.
  - `97-99`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.

```

Value

numeric The calculated adjusted total household income as a numeric. If inputs are invalid or out of bounds, the function returns a tagged NA.

See Also

[categorize_income_quintile\(\)](#) for income classification, [is_lowest_income_quintile\(\)](#) for poverty indicators

Examples

```

# Scalar usage: Single respondent
# Example 1: Respondent with $50,000 income and a household size of 3.
calculate_household_income(thi_01 = 50000, dhhdsz = 3)
# Output: 29411.76

# Example 2: Respondent has non-response values for all inputs.
result <- calculate_household_income(thi_01 = 99999998, dhhdsz = 98)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

# Multiple respondents
calculate_household_income(thi_01 = c(50000, 75000, 90000), dhhdsz = c(3, 2, 1))
# Returns: c(29411.76, 53571.43, 90000)

```

```
# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(adj_hh_income = calculate_household_income(thi_01, dhhhsz)) |>
  head()
```

calculate_nonhdl	<i>Non-HDL cholesterol level</i>
------------------	----------------------------------

Description

This function calculates a respondent's non-HDL cholesterol level by subtracting their HDL cholesterol level from their total cholesterol level. It first checks whether the input values `lab_chol` (total cholesterol) and `lab_hdl` (HDL cholesterol) are within valid ranges.

Usage

```
calculate_nonhdl(lab_chol, lab_hdl)
```

Arguments

`lab_chol` **numeric** A numeric representing a respondent's total cholesterol level in mmol/L.
`lab_hdl` **numeric** A numeric representing a respondent's HDL cholesterol level in mmol/L.

Details

The function calculates the non-HDL cholesterol level by subtracting the HDL cholesterol level from the total cholesterol level.

```
**Missing Data Codes:**
- `lab_chol`:
  - `99.96`: Valid skip. Handled as `haven::tagged_na("a")`.
  - `99.97-99.99`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.
- `lab_hdl`:
  - `9.96`: Valid skip. Handled as `haven::tagged_na("a")`.
  - `9.97-9.99`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.
```

Value

numeric The calculated non-HDL cholesterol level (in mmol/L). If inputs are invalid or out of bounds, the function returns a tagged NA.

See Also

[categorize_nonhdl\(\)](#)

Examples

```
# Scalar usage: Single respondent
# Example: Respondent has total cholesterol of 5.0 mmol/L and HDL cholesterol of 1.5 mmol/L.
calculate_nonhdl(lab_chol = 5.0, lab_hdl = 1.5)
# Output: 3.5

# Example: Respondent has non-response values for cholesterol.
result <- calculate_nonhdl(lab_chol = 99.98, lab_hdl = 1.5)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

# Multiple respondents
calculate_nonhdl(lab_chol = c(5.0, 6.0, 7.0), lab_hdl = c(1.5, 1.0, 2.0))
# Returns: c(3.5, 5.0, 5.0)

# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(non_hdl = calculate_nonhdl(lab_chol, lab_hdl)) |>
  head()
```

calculate_pack_years *Smoking pack-years*

Description

This function calculates an individual's smoking pack-years based on various CHMS smoking variables. Pack years is a measure used by researchers to quantify lifetime exposure to cigarette use.

Usage

```
calculate_pack_years(  
  smkdsty,  
  clc_age,  
  smk_54,  
  smk_52,  
  smk_31,  
  smk_41,  
  smk_53,  
  smk_42,  
  smk_21,  
  smk_11  
)
```

Arguments

smkdsty	integer An integer representing the smoking status of the respondent.
clc_age	numeric A numeric representing the respondent's age.
smk_54	numeric A numeric representing the respondent's age when they stopped smoking daily.
smk_52	numeric A numeric representing the respondent's age when they first started smoking daily.
smk_31	integer An integer representing the number of cigarettes smoked per day for daily smokers.
smk_41	numeric A numeric representing the number of cigarettes smoked per day for occasional smokers.
smk_53	numeric A numeric representing the number of cigarettes smoked per day for former daily smokers.
smk_42	numeric A numeric representing the number of days in past month the respondent smoked at least 1 cigarette (for occasional smokers).
smk_21	numeric A numeric representing the respondent's age when they first started smoking occasionally.
smk_11	integer An integer representing whether the respondent has smoked at least 100 cigarettes in their lifetime.

Details

Pack-years is a standardized measure of lifetime cigarette exposure used in epidemiological research and clinical practice. The calculation varies by smoking pattern:

****Smoking Patterns:****

- Daily smokers: Consistent daily consumption over time period
- Occasional smokers: Variable consumption adjusted for frequency
- Former smokers: Historical consumption during smoking periods

****Minimum Values:****

The function applies minimum pack-year values (0.0137 or 0.007) to prevent underestimation of health risks for light smokers.

****Missing Data Codes:****

- `smkdsty`: `96` (Not applicable), `97-99` (Missing)
- `clc_age`: `96` (Not applicable), `97-99` (Missing)
- Other variables: Handled within the formula logic.

Value

numeric A numeric representing the pack years for the respondent's smoking history. If inputs are invalid or out of bounds, the function returns a tagged NA.

See Also

https://big-life-lab.github.io/cchsflow/reference/calculate_pack_years.html

Examples

```

# Scalar usage: Single respondent
# A former occasional smoker who smoked at least 100 cigarettes in their lifetime.
calculate_pack_years(
  smkdsty = 5, clc_age = 50, smk_54 = 40, smk_52 = 18, smk_31 = NA,
  smk_41 = 15, smk_53 = NA, smk_42 = 3, smk_21 = 25, smk_11 = 1
)
# Output: 0.0137

# Example: Respondent has non-response values for all inputs.
result <- calculate_pack_years(
  smkdsty = 98, clc_age = 998, smk_54 = 98, smk_52 = 98, smk_31 = 98,
  smk_41 = 98, smk_53 = 98, smk_42 = 98, smk_21 = 98, smk_11 = 8
)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

# Multiple respondents
calculate_pack_years(
  smkdsty = c(1, 5, 6),
  clc_age = c(40, 50, 60),
  smk_52 = c(20, 18, NA),
  smk_31 = c(30, NA, NA),
  smk_54 = c(NA, 40, NA),
  smk_41 = c(NA, 15, NA),
  smk_53 = c(NA, NA, NA),
  smk_42 = c(NA, 3, NA),
  smk_21 = c(NA, 25, NA),
  smk_11 = c(NA, 1, NA)
)
# Returns: c(30, 0.0137, 0)

# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(pack_years = calculate_pack_years(smkdsty, clc_age, smk_54, smk_52,
    smk_31, smk_41, smk_53, smk_42, smk_21, smk_11)) |>
  head()

```

calculate_waist_height_ratio

Waist-to-height ratio (WHtR)

Description

This function calculates the Waist-to-Height Ratio (WHtR) by dividing the waist circumference by the height of the respondent.

Usage

```
calculate_waist_height_ratio(hwm_11cm, hwm_14cx)
```

Arguments

`hwm_11cm` **numeric** A numeric representing the height of the respondent in centimeters.

`hwm_14cx` **numeric** A numeric representing the waist circumference of the respondent in centimeters.

Details

This function calculates the Waist-to-Height Ratio (WHtR), an indicator of central obesity.

```
**Missing Data Codes:**
- `hwm_11cm`:
  - `999.96`: Valid skip. Handled as `haven::tagged_na("a")`.
- `999.97-999.99`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.
- `hwm_14cx`:
  - `999.6`: Valid skip. Handled as `haven::tagged_na("a")`.
- `999.7-999.9`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.
```

Value

numeric The WHtR. If inputs are invalid or out of bounds, the function returns a tagged NA.

Examples

```
# Scalar usage: Single respondent
# Example 1: Calculate WHtR for a respondent with height = 170 cm and waist circumference = 85 cm.
calculate_waist_height_ratio(hwm_11cm = 170, hwm_14cx = 85)
# Output: 0.5 (85/170)

# Example 2: Calculate WHtR for a respondent with missing height.
result <- calculate_waist_height_ratio(hwm_11cm = 999.98, hwm_14cx = 85)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

# Multiple respondents
calculate_waist_height_ratio(hwm_11cm = c(170, 180, 160), hwm_14cx = c(85, 90, 80))
# Returns: c(0.5, 0.5, 0.5)

# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(whtr = calculate_waist_height_ratio(hwm_11cm, hwm_14cx)) |>
  head()
```

categorize_ckd	<i>Chronic kidney disease (CKD) derived variable</i>
----------------	--

Description

This function categorizes individuals' glomerular filtration rate (GFR) into stages of Chronic Kidney Disease (CKD).

Usage

```
categorize_ckd(gfr)
```

Arguments

`gfr` **numeric** A numeric representing the glomerular filtration rate.

Details

This function applies the Kidney Disease: Improving Global Outcomes (KDIGO) guideline to classify Chronic Kidney Disease (CKD) based on GFR.

****Missing Data Codes:****

- Propagates tagged NAs from the input ``gfr``.

Value

integer The CKD stage:

- 1: GFR of 60 or below (indicating CKD)
- 2: GFR above 60 (not indicating CKD)
- `haven::tagged_na("a")`: Not applicable
- `haven::tagged_na("b")`: Missing

References

Kidney Disease: Improving Global Outcomes (KDIGO) CKD Work Group. (2013). KDIGO 2012 clinical practice guideline for the evaluation and management of chronic kidney disease. *Kidney international supplements*, 3(1), 1-150.

See Also

[calculate_gfr\(\)](#)

Examples

```
# Scalar usage: Single respondent
# Example 1: Categorize a GFR of 45
categorize_ckd(45)
# Output: 1

# Example 2: Categorize a GFR of 75
categorize_ckd(75)
# Output: 2

# Example 3: Respondent has a non-response value for GFR.
result <- categorize_ckd(haven::tagged_na("b"))
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

# Multiple respondents
categorize_ckd(c(45, 75, 60))
# Returns: c(1, 2, 1)

# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(gfr = calculate_gfr(lab_bcre, pgdcgt, clc_sex, clc_age)) |>
  mutate(ckd = categorize_ckd(gfr)) |>
  head()
```

categorize_diet_quality

Categorical diet indicator

Description

This function categorizes individuals' diet quality based on their total fruit and vegetable consumption.

Usage

```
categorize_diet_quality(fv_daily)
```

Arguments

`fv_daily` **numeric** A numeric vector representing the average times per day fruits and vegetables were consumed in a year.

Details

This function categorizes diet quality based on the widely recognized "5-a-day" recommendation for fruit and vegetable intake.

```
**Missing Data Codes:**  
- Propagates tagged NAs from the input `fv_daily`.
```

Value

[integer](#) A categorical indicating the diet quality:

- 1: Good diet (fv_daily >= 5)
- 2: Poor diet (fv_daily < 5)
- haven::tagged_na("a"): Valid skip
- haven::tagged_na("b"): Missing

See Also

[calculate_fv_daily_cycles1to2\(\)](#), [calculate_fv_daily_cycles3to6\(\)](#)

Examples

```
# Scalar usage: Single respondent  
# Example 1: Categorize a fv_daily value of 3 as poor diet  
categorize_diet_quality(3)  
# Output: 2  
  
# Example 2: Categorize a fv_daily value of 7 as good diet  
categorize_diet_quality(7)  
# Output: 1  
  
# Multiple respondents  
categorize_diet_quality(c(3, 7, 5))  
# Returns: c(2, 1, 1)  
  
# Database usage: Applied to survey datasets  
library(dplyr)  
cycle4 |>  
  mutate(total_fv = calculate_fv_daily_cycles3to6(wsdd34y, wsdd35y, gfvd17ay,  
    gfvd17by, gfvd17cy, gfvd17dy, gfvd18y, gfvd19y, gfvd20y, gfvd22y, gfvd23y)) |>  
  mutate(diet_quality = categorize_diet_quality(total_fv)) |>  
  head()
```

categorize_exercise	<i>Categorical weekly moderate-to-vigorous physical activity (MVPA) indicator</i>
---------------------	---

Description

This function categorizes individuals' weekly moderate-to-vigorous physical activity (MVPA) levels against the 150 minutes/week guideline.

Usage

```
categorize_exercise(exercise_min_week)
```

Arguments

`exercise_min_week`

numeric A numeric representing an individual's minutes of moderate-to-vigorous physical activity (MVPA) per week.

Details

This function applies the national physical activity guideline of 150 minutes of moderate-to-vigorous physical activity (MVPA) per week.

****Missing Data Codes:****

- Propagates tagged NAs from the input ``exercise_min_week``.

Value

integer A categorical indicating the MVPA category:

- 1: Meets or exceeds the recommended 150 minutes of MVPA per week (`exercise_min_week >= 150`)
- 2: Below the recommended 150 minutes of MVPA per week (`exercise_min_week < 150`)
- `haven::tagged_na("a")`: Not applicable
- `haven::tagged_na("b")`: Missing

See Also

[calculate_exercise_weekly\(\)](#)

Examples

```

# Scalar usage: Single respondent
# Example 1: Categorize 180 minutes of MVPA per week as meeting the recommendation
categorize_exercise(180)
# Output: 1

# Example 2: Categorize 120 minutes of MVPA per week as below the recommendation
categorize_exercise(120)
# Output: 2

# Multiple respondents
categorize_exercise(c(180, 120, 150))
# Returns: c(1, 2, 1)

# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(avg_exercise = calculate_exercise_daily_avg(ammdmva1, ammdmva2,
    ammdmva3, ammdmva4, ammdmva5, ammdmva6, ammdmva7)) |>
  mutate(min_per_week = calculate_exercise_weekly(avg_exercise)) |>
  mutate(pa_category = categorize_exercise(min_per_week)) |>
  head()

```

categorize_income_quintile

Categorical adjusted household income

Description

This function categorizes individuals' adjusted household income based on specified income ranges.

Usage

```
categorize_income_quintile(adj_hh_income)
```

Arguments

adj_hh_income **numeric** A numeric representing the adjusted household income.

Details

This function segments adjusted household income into quintiles, providing a standardized measure of socioeconomic status.

****Missing Data Codes:****

- Propagates tagged NAs from the input `adj_hh_income`.

Value

integer The income category:

- 1: Below or equal to \$21,500
- 2: Above \$21,500 and up to \$35,000
- 3: Above \$35,000 and up to \$50,000
- 4: Above \$50,000 and up to \$70,000
- 5: Above \$70,000
- haven::tagged_na("a"): Not applicable
- haven::tagged_na("b"): Missing

See Also

[calculate_household_income\(\)](#), [is_lowest_income_quintile\(\)](#)

Examples

```
# Scalar usage: Single respondent
# Example 1: Categorize a household income of $25,000
categorize_income_quintile(25000)
# Output: 2

# Example 2: Categorize a household income of $45,000
categorize_income_quintile(45000)
# Output: 3

# Multiple respondents
categorize_income_quintile(c(25000, 45000, 80000))
# Returns: c(2, 3, 5)

# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(adj_hh_income = calculate_household_income(thi_01, dhhdhsz)) |>
  mutate(income_category = categorize_income_quintile(adj_hh_income)) |>
  head()
```

categorize_nonhdl *Categorical non-HDL cholesterol level*

Description

This function categorizes individuals' non-HDL cholesterol levels based on a threshold value.

Usage

```
categorize_nonhdl(nonhdl)
```

Arguments

`nonhdl` **numeric** A numeric representing an individual's non-HDL cholesterol level.

Details

This function categorizes non-HDL cholesterol levels into 'High' or 'Normal' based on a 4.3 mmol/L threshold.

```
**Missing Data Codes:**  
- Propagates tagged NAs from the input `nonhdl`.
```

Value

integer A categorical indicating the non-HDL cholesterol category:

- 1: High non-HDL cholesterol ($\text{nonhdl} \geq 4.3$)
- 2: Normal non-HDL cholesterol ($\text{nonhdl} < 4.3$)
- `haven::tagged_na("a")`: Not applicable
- `haven::tagged_na("b")`: Missing

See Also

[calculate_nonhdl\(\)](#)

Examples

```
# Scalar usage: Single respondent  
# Example 1: Categorize a nonhdl value of 5.0 as high non-HDL cholesterol  
categorize_nonhdl(5.0)  
# Output: 1  
  
# Example 2: Categorize a nonhdl value of 3.8 as normal non-HDL cholesterol  
categorize_nonhdl(3.8)  
# Output: 2  
  
# Multiple respondents  
categorize_nonhdl(c(5.0, 3.8, 4.3))  
# Returns: c(1, 2, 1)  
  
# Database usage: Applied to survey datasets  
library(dplyr)  
cycle4 |>  
  mutate(non_hdl = calculate_nonhdl(lab_chol, lab_hdl)) |>  
  mutate(non_hdl_category = categorize_nonhdl(non_hdl)) |>  
  head()
```

`cycle1`*Canadian Health Measures Survey (CHMS) Cycle 1*

Description

This is dummy data representing the second cycle of the Canadian Health Measures Survey (CHMS). The CHMS survey is conducted by Statistics Canada.

Usage

```
data(cycle1)
```

Source

Statistics Canada

Examples

```
data(cycle1)
str(cycle1)
```

`cycle1_meds`*Canadian Health Measures Survey (CHMS) Cycle 1 Medications*

Description

This dummy data representing the medication portion of the second cycle of the Canadian Health Measures Survey (CHMS). The CHMS survey is conducted by Statistics Canada.

Usage

```
data(cycle1_meds)
```

Format

A data frame with X rows and Y columns.

Source

Statistics Canada

Examples

```
data(cycle1_meds)
str(cycle1_meds)
```

`cycle2`*Canadian Health Measures Survey (CHMS) Cycle 2*

Description

This is dummy data representing the second cycle of the Canadian Health Measures Survey (CHMS). The CHMS survey is conducted by Statistics Canada.

Usage

```
data(cycle2)
```

Source

Statistics Canada

Examples

```
data(cycle2)
str(cycle2)
```

`cycle2_meds`*Canadian Health Measures Survey (CHMS) Cycle 2 Medications*

Description

This dummy data representing the medication portion of the second cycle of the Canadian Health Measures Survey (CHMS). The CHMS survey is conducted by Statistics Canada.

Usage

```
data(cycle2_meds)
```

Source

Statistics Canada

Examples

```
data(cycle2_meds)
str(cycle2_meds)
```

`cycle3`*Canadian Health Measures Survey (CHMS) Cycle 3*

Description

This is dummy data representing the third cycle of the Canadian Health Measures Survey (CHMS). The CHMS survey is conducted by Statistics Canada.

Usage

```
data(cycle3)
```

Source

Statistics Canada

Examples

```
data(cycle3)
str(cycle3)
```

`cycle3_meds`*Canadian Health Measures Survey (CHMS) Cycle 3 Medications*

Description

This dummy data representing the medication portion of the third cycle of the Canadian Health Measures Survey (CHMS). The CHMS survey is conducted by Statistics Canada.

Usage

```
data(cycle3_meds)
```

Source

Statistics Canada

Examples

```
data(cycle3_meds)
str(cycle3_meds)
```

`cycle4`*Canadian Health Measures Survey (CHMS) Cycle 4*

Description

This is dummy data representing the fourth cycle of the Canadian Health Measures Survey (CHMS). The CHMS survey is conducted by Statistics Canada.

Usage

```
data(cycle4)
```

Source

Statistics Canada

Examples

```
data(cycle4)
str(cycle4)
```

`cycle4_meds`*Canadian Health Measures Survey (CHMS) Cycle 4 Medications*

Description

This dummy data representing the medication portion of the third cycle of the Canadian Health Measures Survey (CHMS). The CHMS survey is conducted by Statistics Canada.

Usage

```
data(cycle4_meds)
```

Source

Statistics Canada

Examples

```
data(cycle4_meds)
str(cycle4_meds)
```

`cycle5`*Canadian Health Measures Survey (CHMS) Cycle 5*

Description

This is dummy data representing the fifth cycle of the Canadian Health Measures Survey (CHMS). The CHMS survey is conducted by Statistics Canada.

Usage

```
data(cycle5)
```

Source

Statistics Canada

Examples

```
data(cycle5)
str(cycle5)
```

`cycle5_meds`*Canadian Health Measures Survey (CHMS) Cycle 5 Medications*

Description

This dummy data representing the medication portion of the third cycle of the Canadian Health Measures Survey (CHMS). The CHMS survey is conducted by Statistics Canada.

Usage

```
data(cycle5_meds)
```

Source

Statistics Canada

Examples

```
data(cycle5_meds)
str(cycle5_meds)
```

`cycle6`*Canadian Health Measures Survey (CHMS) Cycle 6*

Description

This is dummy data representing the fifth cycle of the Canadian Health Measures Survey (CHMS). The CHMS survey is conducted by Statistics Canada.

Usage

```
data(cycle6)
```

Source

Statistics Canada

Examples

```
data(cycle6)
str(cycle6)
```

`cycle6_meds`*Canadian Health Measures Survey (CHMS) Cycle 6 Medications*

Description

This dummy data representing the medication portion of the third cycle of the Canadian Health Measures Survey (CHMS). The CHMS survey is conducted by Statistics Canada.

Usage

```
data(cycle6_meds)
```

Source

Statistics Canada

Examples

```
data(cycle6_meds)
str(cycle6_meds)
```

derive_alcohol_risk *Low risk drinking score*

Description

This function calculates a low drink score (step 1 only) for a respondent using Canada's Low-Risk Alcohol Drinking Guideline. The score is based solely on the number of standard drinks consumed per week and the respondent's sex. (Step 2, which would add additional points based on other drinking habits, is not included.).

Usage

```
derive_alcohol_risk(clc_sex, alc_11, alcdwky)
```

Arguments

clc_sex	integer An integer indicating the respondent's sex (1 for male, 2 for female).
alc_11	integer An integer indicating whether the respondent drank alcohol in the past year (1 for "Yes", 2 for "No").
alcdwky	integer An integer representing the number of standard drinks consumed by the respondent in a week.

Details

The scoring is determined by first allocating points (referred to as step1) based on the weekly alcohol consumption and the respondent's sex:

- If the respondent drank in the past year (alc_11 == 1):
 - For alcdwky <= 10, assign 0 points.
 - For alcdwky > 10 and <= 15: assign 0 points for males (clc_sex == 1) and 1 point for females (clc_sex == 2).
 - For alcdwky > 15 and <= 20: assign 1 point for males and 3 points for females.
 - For alcdwky > 20: assign 3 points.
- For respondents who did not drink in the past year (alc_11 == 2), 0 points are assigned.

These step1 points are then mapped to the final categorical score as follows:

- 0 points -> score of 1 ("Low risk"),
- 1-2 points -> score of 2 ("Marginal risk"),
- 3-4 points -> score of 3 ("Medium risk"),
- 5-9 points -> score of 4 ("High risk").

This function implements Canada's Low-Risk Alcohol Drinking Guidelines (Step 1 only) to assess alcohol consumption risk. The scoring system considers both the quantity of alcohol consumed and biological sex differences in alcohol metabolism.

Risk Categories:

- Low risk (0 points): Safe consumption levels
- Marginal risk (1-2 points): Slightly elevated risk
- Medium risk (3-4 points): Moderate health concerns
- High risk (5-9 points): Significant health risks

Sex-Based Differences: Women generally have lower tolerance thresholds due to physiological differences in alcohol metabolism, reflected in the sex-specific point allocations.

Non-response Handling: Invalid inputs or survey non-response values result in tagged NA ("b").

Value

`integer` The low drink score, with:

- 1 for "Low risk" (0 points),
- 2 for "Marginal risk" (1-2 points),
- 3 for "Medium risk" (3-4 points), and
- 4 for "High risk" (5-9 points). If inputs are invalid or out of bounds, the function returns a tagged NA.

Note

This function implements only Step 1 of the guidelines. Step 2 (additional drinking pattern assessments) is not included due to data limitations in the survey.

References

Canada's Low-Risk Alcohol Drinking Guidelines, Health Canada

See Also

`derive_alcohol_risk_detailed()` for extended categorization including former/never drinkers

Examples

```
# Scalar usage: Single respondent
# Example: A male respondent who drank in the past year and consumes 3 standard drinks per week.
derive_alcohol_risk(clc_sex = 1, alc_11 = 1, alcdwky = 3)
# Expected output: 1 (Low risk)

# Missing data examples showing tagged NA patterns
result <- derive_alcohol_risk(clc_sex = 1, alc_11 = 6, alcdwky = 5)
result # Shows: NA
haven::is_tagged_na(result, "a") # Shows: TRUE (confirms it's tagged NA(a))
format(result, tag = TRUE) # Shows: "NA(a)" (displays the tag)

result <- derive_alcohol_risk(clc_sex = 1, alc_11 = 7, alcdwky = 5)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)
```

```

result <- derive_alcohol_risk(clc_sex = 1, alc_11 = 1, alcdwky = NA)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

# Multiple respondents
derive_alcohol_risk(clc_sex = c(1, 2, 1), alc_11 = c(1, 1, 2), alcdwky = c(3, 12, NA))
# Returns: c(1, 2, 1)

# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(alc_risk_score = derive_alcohol_risk(clc_sex, alc_11, alcdwky)) |>
  head()

```

derive_alcohol_risk_detailed

Low risk drinking score - former/never categories

Description

Computes a categorical alcohol consumption score based on Canada's Low-Risk Alcohol Drinking Guidelines (Step 1), while distinguishing between never, former, light, moderate, and heavy drinkers. The function uses information about weekly consumption, past-year use, lifetime drinking, and history of heavy drinking.

Usage

```
derive_alcohol_risk_detailed(clc_sex, alc_11, alcdwky, alc_17, alc_18)
```

Arguments

clc_sex	integer Respondent's sex (1 = male, 2 = female).
alc_11	integer Whether the respondent drank alcohol in the past year (1 = Yes, 2 = No).
alcdwky	integer Number of standard drinks consumed in a typical week (0-84).
alc_17	integer Whether the respondent ever drank alcohol in their lifetime (1 = Yes, 2 = No).
alc_18	integer Whether the respondent regularly drank more than 12 drinks per week (1 = Yes, 2 = No).

Details

Step 1: Assign points based on weekly alcohol consumption.

- If the respondent drank in the past year (`alc_11 == 1`):

- 0 to 10 drinks/week: 0 points
- 11 to 15 drinks/week: 0 points for males, 1 point for females
- 16 to 20 drinks/week: 1 point for males, 3 points for females
- More than 20 drinks/week: 3 points for males, 5 points for females
- If they did not drink in the past year (`alc_11 == 2`): 0 points

Step 2: Determine the final categorical score.

- If the point score from Step 1 is 0, the final category is determined based on lifetime and past-year drinking habits:
 - A score of 1 (Never drinker) is assigned if the respondent either never drank alcohol in their lifetime or is a former drinker who did not regularly consume more than 12 drinks a week.
 - A score of 2 (Low-risk drinker) is assigned if the respondent drank in the past year (but still scored 0 points) or is a former drinker with a history of regularly consuming more than 12 drinks a week.
- If the point score from Step 1 is 1 or 2, the respondent is classified as a Moderate drinker (Score = 3).
- If the point score from Step 1 is 3 or more, the respondent is classified as a Heavy drinker (Score = 4). If inputs are invalid or out of bounds, the function returns a tagged NA.

Value

integer Score: 1 = Never drank, 2 = Low-risk (former or light) drinker, 3 = Moderate drinker (1–2 points), 4 = Heavy drinker (3–4 points). If inputs are invalid or out of bounds, the function returns a tagged NA.

Note

This function uses only Step 1 of the guidelines, as Step 2 information is unavailable in CHMS.

References

Canada's Low-Risk Alcohol Drinking Guidelines, Health Canada

See Also

[derive_alcohol_risk\(\)](#) for basic risk scoring without drinking history

Examples

```
# Scalar usage: Single respondent
# Example: Male, drinks 3 drinks/week, drank in past year, no history of heavy drinking
derive_alcohol_risk_detailed(
  clc_sex = 1, alc_11 = 1, alcdwky = 3,
  alc_17 = 1, alc_18 = 2
)
# Expected output: 2
```

```

# Missing data examples showing tagged NA patterns
result <- derive_alcohol_risk_detailed(
  clc_sex = 1, alc_11 = 6, alcdwky = 5,
  alc_17 = 1, alc_18 = 2
)
result # Shows: NA
haven::is_tagged_na(result, "a") # Shows: TRUE (confirms it's tagged NA(a))
format(result, tag = TRUE) # Shows: "NA(a)" (displays the tag)

result <- derive_alcohol_risk_detailed(
  clc_sex = 1, alc_11 = 7, alcdwky = 5,
  alc_17 = 1, alc_18 = 2
)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

result <- derive_alcohol_risk_detailed(
  clc_sex = 1, alc_11 = 1, alcdwky = NA,
  alc_17 = 1, alc_18 = 2
)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

# Multiple respondents
derive_alcohol_risk_detailed(
  clc_sex = c(1, 2, 1), alc_11 = c(1, 1, 2),
  alcdwky = c(3, 12, NA), alc_17 = c(1, 1, 1), alc_18 = c(2, 2, 1)
)
# Returns: c(2, 3, 2)

# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(alc_detailed_risk_score = derive_alcohol_risk_detailed(
    clc_sex, alc_11, alcdwky, alc_17, alc_18)) |>
  head()

```

derive_cvd_family_history

Cardiovascular Disease (CVD) family history

Description

This function evaluates a respondent's family history of cardiovascular disease (CVD), based on data about diagnoses of heart disease and stroke in immediate family members and the ages at which these diagnoses occurred. It identifies premature CVD if any diagnosis occurred before age 60.

Usage

```
derive_cvd_family_history(fmh_11, fmh_12, fmh_13, fmh_14)
```

Arguments

fmh_11	integer An integer: Indicates whether an immediate family member was diagnosed with heart disease. - 1 for "Yes" - 2 for "No".
fmh_12	numeric A numeric: Represents the youngest age at diagnosis of heart disease in an immediate family member.
fmh_13	integer An integer: Indicates whether an immediate family member was diagnosed with stroke. - 1 for "Yes" - 2 for "No".
fmh_14	numeric A numeric: Represents the youngest age at diagnosis of stroke in an immediate family member.

Details

This function assesses family history of premature cardiovascular disease (CVD), a significant risk factor for personal CVD development.

```

**Missing Data Codes:**
- `fmh_11`, `fmh_13`:
  - `6`: Valid skip. Handled as `haven::tagged_na("a")`.
  - `7-9`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.
- `fmh_12`, `fmh_14`:
  - `996`: Valid skip. Handled as `haven::tagged_na("a")`.
  - `997-999`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.

```

Value

integer The CVD family history:

- 1: "Yes" – Family history of premature CVD exists (diagnosis before age 60).
- 2: "No" – No family history of premature CVD.
- `haven::tagged_na("a")`: Not applicable
- `haven::tagged_na("b")`: Missing

See Also

[derive_cvd_personal_history\(\)](#)

Examples

```

# Scalar usage: Single respondent
# Example 1: Premature CVD due to heart disease diagnosis at age 50
derive_cvd_family_history(fmh_11 = 1, fmh_12 = 50, fmh_13 = 2, fmh_14 = NA)
# Output: 1

# Example 2: Respondent has non-response values for all inputs.

```

```

result <- derive_cvd_family_history(fmh_11 = 8, fmh_12 = 998, fmh_13 = 8, fmh_14 = 998)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

# Multiple respondents
derive_cvd_family_history(
  fmh_11 = c(1, 2, 1), fmh_12 = c(50, NA, 70),
  fmh_13 = c(2, 1, 2), fmh_14 = c(NA, 55, NA)
)
# Returns: c(1, 1, 2)

# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(cvd_family_history = derive_cvd_family_history(fmh_11, fmh_12, fmh_13, fmh_14)) |>
  head()

```

```
derive_cvd_personal_history
```

Cardiovascular disease (CVD) personal history

Description

This function determines a respondent's cardiovascular disease (CVD) personal history based on the presence or absence of specific conditions related to heart disease, heart attack, and stroke.

Usage

```
derive_cvd_personal_history(ccc_61, ccc_63, ccc_81)
```

Arguments

ccc_61	integer An integer representing the respondent's personal history of heart disease. 1 for "Yes" if the person has heart disease, 2 for "No" if the person does not have heart disease.
ccc_63	integer An integer representing the respondent's personal history of heart attack. 1 for "Yes" if the person had a heart attack, 2 for "No" if the person did not have a heart attack.
ccc_81	integer An integer representing the respondent's personal history of stroke. 1 for "Yes" if the person had a stroke, 2 for "No" if the person did not have a stroke.

Details

This function synthesizes self-reported data on major cardiovascular events (heart disease, heart attack, stroke) into a single binary indicator.

****Missing Data Codes:****

- For all input variables:
 - `6`: Valid skip. Handled as `haven::tagged_na("a")`.
 - `7-9`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.

Value

integer The CVD personal history: - 1: "Yes" if the person had heart disease, heart attack, or stroke. - 2: "No" if the person had neither of the conditions. - `haven::tagged_na("a")`: Not applicable - `haven::tagged_na("b")`: Missing

See Also

[derive_cvd_family_history\(\)](#)

Examples

```
# Scalar usage: Single respondent
# Determine CVD personal history for a person with heart disease (ccc_61 = 1).
derive_cvd_personal_history(ccc_61 = 1, ccc_63 = 2, ccc_81 = 2)
# Output: 1

# Example: Respondent has non-response values for all inputs.
result <- derive_cvd_personal_history(ccc_61 = 8, ccc_63 = 8, ccc_81 = 8)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

# Multiple respondents
derive_cvd_personal_history(ccc_61 = c(1, 2, 2), ccc_63 = c(2, 1, 2), ccc_81 = c(2, 2, 1))
# Returns: c(1, 1, 1)

# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(cvd_personal_history = derive_cvd_personal_history(ccc_61, ccc_63, ccc_81)) |>
  head()
```

derive_diabetes_status

Diabetes derived variable

Description

This function evaluates diabetes status using a comprehensive approach that combines laboratory measurements, self-reported diagnosis, and medication usage to create an inclusive diabetes classification.

Usage

```
derive_diabetes_status(diab_a1c, ccc_51, diab_med)
```

Arguments

diab_a1c [integer](#) An integer indicating whether the respondent has diabetes based on HbA1c level. 1 for "Yes", 2 for "No".

ccc_51 [integer](#) An integer indicating whether the respondent self-reported diabetes. 1 for "Yes", 2 for "No".

diab_med [integer](#) An integer indicating whether the respondent is on diabetes medication. 1 for "Yes", 0 for "No".

Details

This function classifies diabetes status based that considers:

```

**Data Sources:**
- Laboratory: HbA1c levels indicating diabetes (diab_a1c)
- Self-report: Participant-reported diabetes diagnosis (ccc_51)
- Medication: Current diabetes medication usage (diab_med)

**Classification Logic:**
- ANY positive indicator results in diabetes classification
- ALL negative indicators required for "no diabetes" classification
- Sophisticated missing data handling preserves available information

**Missing Data Codes:**
- `diab_a1c`, `diab_med`:
  - Tagged NA "a": Valid skip.
  - Tagged NA "b": Don't know, refusal, or not stated.
- `ccc_51`:
  - `6`: Valid skip. Handled as `haven::tagged_na("a")`.
  - `7-9`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.

```

Value

[integer](#) The inclusive diabetes status: - 1 ("Yes") if any of diab_a1c, ccc_51, or diab_med is 1. - 2 ("No") if all of diab_a1c, ccc_51, and diab_med are 2 or 0. - `haven::tagged_na("a")`: Not applicable - `haven::tagged_na("b")`: Missing

See Also

Related health condition functions: [derive_hypertension\(\)](#), [calculate_gfr\(\)](#)

Examples

```

# Scalar usage: Single respondent
# Example: Determine the inclusive diabetes status for a respondent with diabetes based on HbA1c.
derive_diabetes_status(diab_a1c = 1, ccc_51 = 2, diab_med = 0)

```

```

# Output: 1 (Inclusive diabetes status is "Yes").

# Example: Determine the inclusive diabetes status for a respondent no diabetes all around.
derive_diabetes_status(diab_a1c = 2, ccc_51 = 2, diab_med = 0)
# Output: 2 (Inclusive diabetes status is "No").

# Example: Determine inclusive diabetes status when only one parameter is NA.
derive_diabetes_status(diab_a1c = 2, ccc_51 = NA, diab_med = 1)
# Output: 1 (Based on `diab_med`, inclusive diabetes status is "Yes").

# Example: Respondent has non-response values for all inputs.
result <- derive_diabetes_status(haven::tagged_na("b"), 8, haven::tagged_na("b"))
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

# Multiple respondents
derive_diabetes_status(diab_a1c = c(1, 2, 2), ccc_51 = c(2, 1, 2), diab_med = c(0, 0, 1))
# Returns: c(1, 1, 1)

# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(diab_a1c = 1, diab_med = 0) |>
  mutate(diabetes_status = derive_diabetes_status(diab_a1c, ccc_51, diab_med)) |>
  head()

```

derive_hypertension *Hypertension derived variable*

Description

This function determines the hypertension status of a respondent based on their systolic and diastolic blood pressure measurements and medication usage.

Usage

```

derive_hypertension(
  bpmdbbps,
  bpmdbbpd,
  any_htn_med,
  ccc_32 = 2,
  cvd_status = 2,
  diab_status = 2,
  ckd_status = 2
)

```

Arguments

bpmdbbps	integer An integer representing the systolic blood pressure measurement of the respondent.
bpmdbbpd	integer An integer representing the diastolic blood pressure measurement of the respondent.
any_htn_med	integer An integer indicating whether the respondent is on medication for hypertension. <ul style="list-style-type: none"> • 1: Yes • 0: No
ccc_32	integer An optional integer indicating whether the respondent is actually on medication for hypertension. <ul style="list-style-type: none"> • 1: Yes • 2: No (default)
cvd_status	integer An optional integer indicating the presence of cardiovascular disease, affecting medication status. <ul style="list-style-type: none"> • 1: Yes • 2: No (default)
diab_status	integer An optional integer indicating the presence of diabetes, affecting blood pressure thresholds. <ul style="list-style-type: none"> • 1: Yes • 2: No (default)
ckd_status	integer An optional integer indicating the presence of chronic kidney disease, affecting blood pressure thresholds. <ul style="list-style-type: none"> • 1: Yes • 2: No (default)

Details

This function implements clinical guidelines for hypertension classification:

```

**Blood Pressure Thresholds:**
- General population: >= 140/90 mmHg indicates hypertension
- Diabetes or CKD patients: >= 130/80 mmHg indicates hypertension (lower threshold)

**Medication Logic:**
- Anyone taking hypertension medication is classified as hypertensive
- Medication status may be adjusted based on comorbidities (diabetes, CKD, cardiovascular disease)

**Missing Data Codes:**
- `bpmdbbps`, `bpmdbbpd`:
  - `996`: Valid skip. Handled as `haven::tagged_na("a")`.
- `997-999`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.
- `any_htn_med`:
  - Tagged NA "a": Valid skip.

```

- Tagged NA "b": Don't know, refusal, or not stated.
- `ccc_32`, `cvd_status`, `diab_status`, `ckd_status`:
 - `6`: Valid skip. Handled as `haven::tagged_na("a")`.
 - `7-9`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.

Value

integer The hypertension status:

- 1: High blood pressure (BP \geq 140/90 mmHg (or \geq 130/80 mmHg if diabetes or CKD) or on hypertension medication)
- 2: Normal blood pressure (BP $<$ 140/90 mmHg (or $<$ 130/80 mmHg if diabetes or CKD) and not on hypertension medication)
- `haven::tagged_na("a")`: Not applicable
- `haven::tagged_na("b")`: Missing

See Also

[adjust_sbp\(\)](#), [adjust_dbp\(\)](#) for blood pressure adjustment, [derive_hypertension_adj\(\)](#) for adjusted BP classification

Examples

```
# Scalar usage: Single respondent
# Example 1: Respondent has systolic BP = 150, diastolic BP = 95, and on medication.
derive_hypertension(bpmdpbbps = 150, bpmdpbbpd = 95, any_htn_med = 1)
# Output: 1 (High blood pressure due to systolic BP, diastolic BP, and medication usage).

# Example 2: Respondent has systolic BP = 120, diastolic BP = 80, and not on medication.
derive_hypertension(bpmdpbbps = 120, bpmdpbbpd = 80, any_htn_med = 0)
# Output: 2 (Normal blood pressure as BP is below 140/90 mmHg and not on medication).

# Example 3: Respondent has non-response BP values of 996 for both systolic and diastolic.
result <- derive_hypertension(bpmdpbbps = 996, bpmdpbbpd = 996, any_htn_med = 0)
result # Shows: NA
haven::is_tagged_na(result, "a") # Shows: TRUE (confirms it's tagged NA(a))
format(result, tag = TRUE) # Shows: "NA(a)" (displays the tag)

# Multiple respondents
derive_hypertension(
  bpmdpbbps = c(150, 120, 135), bpmdpbbpd = c(95, 80, 85),
  any_htn_med = c(1, 0, 1), diab_status = c(2, 2, 1)
)
# Returns: c(1, 2, 1)

# Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
  mutate(any_htn_med = 0) |>
  mutate(htn = derive_hypertension(bpmdpbbps, bpmdpbbpd, any_htn_med)) |>
  select(clinicid, bpmdpbbps, bpmdpbbpd, htn) |>
```

```
head()
```

```
derive_hypertension_adj
```

Hypertension derived variable with adjusted blood pressures

Description

This function determines the hypertension status of a respondent based on their adjusted systolic and diastolic blood pressure measurements and medication usage.

Usage

```
derive_hypertension_adj(  
  sbp_adj_mmhg,  
  dbp_adj_mmhg,  
  any_htn_med,  
  ccc_32 = 2,  
  cvd_status = 2,  
  diab_status = 2,  
  ckd_status = 2  
)
```

Arguments

- | | |
|--------------|---|
| sbp_adj_mmhg | integer An integer representing the adjusted systolic blood pressure measurement of the respondent. |
| dbp_adj_mmhg | integer An integer representing the adjusted diastolic blood pressure measurement of the respondent. |
| any_htn_med | integer An integer indicating whether the respondent is on medication for hypertension. <ul style="list-style-type: none">• 1: Yes• 0: No |
| ccc_32 | integer An optional integer indicating whether the respondent is actually on medication for hypertension. <ul style="list-style-type: none">• 1: Yes• 2: No (default) |
| cvd_status | integer An optional integer indicating the presence of cardiovascular disease, affecting medication status. <ul style="list-style-type: none">• 1: Yes• 2: No (default) |
| diab_status | integer An optional integer indicating the presence of diabetes, affecting blood pressure thresholds. |

- 1: Yes
 - 2: No (default)
- ckd_status [integer](#) An optional integer indicating the presence of chronic kidney disease, affecting blood pressure thresholds.
- 1: Yes
 - 2: No (default)

Details

This function implements clinical guidelines for hypertension classification using adjusted blood pressure values:

- ```

Blood Pressure Thresholds:
- General population: >= 140/90 mmHg indicates hypertension
- Diabetes or CKD patients: >= 130/80 mmHg indicates hypertension (lower threshold)

Medication Logic:
- Anyone taking hypertension medication is classified as hypertensive
- Medication status may be adjusted based on comorbidities (diabetes, CKD, cardiovascular disease)

Missing Data Codes:
- `sbp_adj_mmhg`, `dbp_adj_mmhg`:
 - `996`: Valid skip. Handled as `haven::tagged_na("a")`.
- `997-999`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.
- `any_htn_med`:
 - Tagged NA "a": Valid skip.
 - Tagged NA "b": Don't know, refusal, or not stated.
- `ccc_32`, `cvd_status`, `diab_status`, `ckd_status`:
 - `6`: Valid skip. Handled as `haven::tagged_na("a")`.
 - `7-9`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.

```

## Value

[integer](#) The hypertension status:

- 1: High blood pressure (adjusted BP  $\geq$  140/90 mmHg (or  $\geq$  130/80 mmHg if diabetes or CKD) or on hypertension medication)
- 2: Normal blood pressure (adjusted BP  $<$  140/90 mmHg (or  $<$  130/80 mmHg if diabetes or CKD) and not on hypertension medication)
- `haven::tagged_na("a")`: Not applicable
- `haven::tagged_na("b")`: Missing

## See Also

[derive\\_hypertension\(\)](#) for unadjusted BP classification

**Examples**

```

Scalar usage: Single respondent
Example 1: Respondent has adjusted SBP = 150, adjusted DBP = 95, and on medication.
derive_hypertension_adj(sbp_adj_mmhg = 150, dbp_adj_mmhg = 95, any_htn_med = 1)
Output: 1 (High blood pressure due to adjusted SBP, adjusted DBP, and medication usage).

Example 2: Respondent has adjusted SBP = 120, adjusted DBP = 80, and not on medication.
derive_hypertension_adj(sbp_adj_mmhg = 120, dbp_adj_mmhg = 80, any_htn_med = 2)
Output: 2 (Normal blood pressure as adjusted BP is below 140/90 mmHg and not on medication).

Example 3: Respondent has non-response BP values of 996 for both systolic and diastolic.
result <- derive_hypertension_adj(sbp_adj_mmhg = 996, dbp_adj_mmhg = 996, any_htn_med = 0)
result # Shows: NA
haven::is_tagged_na(result, "a") # Shows: TRUE (confirms it's tagged NA(a))
format(result, tag = TRUE) # Shows: "NA(a)" (displays the tag)

Multiple respondents
derive_hypertension_adj(
 sbp_adj_mmhg = c(150, 120, 135), dbp_adj_mmhg = c(95, 80, 85),
 any_htn_med = c(1, 0, 1), diab_status = c(2, 2, 1)
)
Returns: c(1, 2, 1)

Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
 mutate(sbp_adj_mmhg = adjust_sbp(bpmdpbps), dbp_adj_mmhg = adjust_dbp(bpmdpbbpd)) |>
 mutate(any_htn_med = 0) |>
 mutate(htn_adj = derive_hypertension_adj(sbp_adj_mmhg, dbp_adj_mmhg, any_htn_med)) |>
 select(clinid, sbp_adj_mmhg, dbp_adj_mmhg, htn_adj) |>
 head()

```

---

```
derive_hypertension_control
```

*Controlled hypertension derived variable*

---

**Description**

This function determines the controlled hypertension status of a respondent based on their systolic and diastolic blood pressure measurements and medication usage.

**Usage**

```

derive_hypertension_control(
 bpmdpbps,
 bpmdpbbpd,
 any_htn_med,
 ccc_32 = 2,

```

```

 cvd_status = 2,
 diab_status = 2,
 ckd_status = 2
)

```

### Arguments

|             |                                                                                                                                                                                                                  |
|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bpmdbbps    | <b>integer</b> An integer representing the systolic blood pressure measurement of the respondent.                                                                                                                |
| bpmdbbpd    | <b>integer</b> An integer representing the diastolic blood pressure measurement of the respondent.                                                                                                               |
| any_htn_med | <b>integer</b> An integer indicating whether the respondent is on medication for hypertension. <ul style="list-style-type: none"> <li>• 1: Yes</li> <li>• 0: No</li> </ul>                                       |
| ccc_32      | <b>integer</b> An optional integer indicating whether the respondent is actually on medication for hypertension. <ul style="list-style-type: none"> <li>• 1: Yes</li> <li>• 2: No (default)</li> </ul>           |
| cvd_status  | <b>integer</b> An optional integer indicating the presence of cardiovascular disease, affecting medication status. <ul style="list-style-type: none"> <li>• 1: Yes</li> <li>• 2: No (default)</li> </ul>         |
| diab_status | <b>integer</b> An optional integer indicating the presence of diabetes, affecting blood pressure thresholds. <ul style="list-style-type: none"> <li>• 1: Yes</li> <li>• 2: No (default)</li> </ul>               |
| ckd_status  | <b>integer</b> An optional integer indicating the presence of chronic kidney disease, affecting blood pressure thresholds. <ul style="list-style-type: none"> <li>• 1: Yes</li> <li>• 2: No (default)</li> </ul> |

### Details

This function assesses whether a respondent's hypertension is controlled:

**\*\*Control Thresholds:\*\***

- General population: < 140/90 mmHg
- Diabetes or CKD patients: < 130/80 mmHg

**\*\*Logic:\*\***

- Only applies to respondents taking hypertension medication.
- If BP is below the threshold, hypertension is "controlled" (1).
- If BP is at or above the threshold, it is "not controlled" (2).

```

Missing Data Codes:
- `bpmdbbps`, `bpmdbbpd`:
 - `996`: Valid skip. Handled as `haven::tagged_na("a")`.
- `997-999`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.
- `any_htn_med`:
 - Tagged NA "a": Valid skip.
 - Tagged NA "b": Don't know, refusal, or not stated.
- `ccc_32`, `cvd_status`, `diab_status`, `ckd_status`:
 - `6`: Valid skip. Handled as `haven::tagged_na("a")`.
- `7-9`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.

```

## Value

**integer** The hypertension status:

- 1: Hypertension controlled (BP < 140/90 mmHg (or < 130/80 mmHg if diabetes or CKD) when on hypertension medication)
- 2: Hypertension not controlled (BP >= 140/90 mmHg (or >= 130/80 mmHg if diabetes or CKD) when on hypertension medication)
- `haven::tagged_na("a")`: Not applicable
- `haven::tagged_na("b")`: Missing

## See Also

[derive\\_hypertension\\_control\\_adj\(\)](#) for controlled status with adjusted BP

## Examples

```

Scalar usage: Single respondent
Example 1: Respondent has systolic BP = 150, diastolic BP = 95, and on medication.
derive_hypertension_control(bpmdbbps = 150, bpmdbbpd = 95, any_htn_med = 1)
Output: 2 (Hypertension not controlled due to high SBP and SBP despite medication usage).

Example 2: Respondent has systolic BP = 120, diastolic BP = 80, and on medication.
derive_hypertension_control(bpmdbbps = 120, bpmdbbpd = 80, any_htn_med = 1)
Output: 1 (Hypertension controlled as BP is below 140/90 mmHg and on medication).

Example 3: Respondent has non-response BP values of 996 for both systolic and diastolic.
result <- derive_hypertension_control(bpmdbbps = 996, bpmdbbpd = 996, any_htn_med = 0)
result # Shows: NA
haven::is_tagged_na(result, "a") # Shows: TRUE (confirms it's tagged NA(a))
format(result, tag = TRUE) # Shows: "NA(a)" (displays the tag)

Multiple respondents
derive_hypertension_control(
 bpmdbbps = c(150, 120, 135), bpmdbbpd = c(95, 80, 85),
 any_htn_med = c(1, 1, 1), diab_status = c(2, 2, 1)
)
Returns: c(2, 1, 2)

```

```
Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
 mutate(any_htn_med = 1) |>
 mutate(ctrl = derive_hypertension_control(bpmdpbps, bpmdpbbpd, any_htn_med)) |>
 select(clinicid, bpmdpbps, bpmdpbbpd, ctrl) |>
 head()
```

---

derive\_hypertension\_control\_adj

*Controlled hypertension derived variable with adjusted blood pressures*

---

### Description

This function determines the controlled hypertension status of a respondent based on their adjusted systolic and diastolic blood pressure measurements and medication usage.

### Usage

```
derive_hypertension_control_adj(
 sbp_adj_mmhg,
 dbp_adj_mmhg,
 any_htn_med,
 ccc_32 = 2,
 cvd_status = 2,
 diab_status = 2,
 ckd_status = 2
)
```

### Arguments

|              |                                                                                                                                                                                                        |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| sbp_adj_mmhg | <b>integer</b> An integer representing the adjusted systolic blood pressure measurement of the respondent.                                                                                             |
| dbp_adj_mmhg | <b>integer</b> An integer representing the adjusted diastolic blood pressure measurement of the respondent.                                                                                            |
| any_htn_med  | <b>integer</b> An integer indicating whether the respondent is on medication for hypertension. <ul style="list-style-type: none"> <li>• 1: Yes</li> <li>• 0: No</li> </ul>                             |
| ccc_32       | <b>integer</b> An optional integer indicating whether the respondent is actually on medication for hypertension. <ul style="list-style-type: none"> <li>• 1: Yes</li> <li>• 2: No (default)</li> </ul> |

|             |                                                                                                                                                                                                                  |
|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| cvd_status  | <b>integer</b> An optional integer indicating the presence of cardiovascular disease, affecting medication status. <ul style="list-style-type: none"> <li>• 1: Yes</li> <li>• 2: No (default)</li> </ul>         |
| diab_status | <b>integer</b> An optional integer indicating the presence of diabetes, affecting blood pressure thresholds. <ul style="list-style-type: none"> <li>• 1: Yes</li> <li>• 2: No (default)</li> </ul>               |
| ckd_status  | <b>integer</b> An optional integer indicating the presence of chronic kidney disease, affecting blood pressure thresholds. <ul style="list-style-type: none"> <li>• 1: Yes</li> <li>• 2: No (default)</li> </ul> |

## Details

This function assesses whether a respondent's hypertension is controlled using adjusted BP values:

```

Control Thresholds:
- General population: < 140/90 mmHg
- Diabetes or CKD patients: < 130/80 mmHg

Logic:
- Only applies to respondents taking hypertension medication.
- If adjusted BP is below the threshold, hypertension is "controlled" (1).
- If adjusted BP is at or above the threshold, it is "not controlled" (2).

Missing Data Codes:
- `sbp_adj_mmhg`, `dbp_adj_mmhg`:
 - `996`: Valid skip. Handled as `haven::tagged_na("a")`.
- `997-999`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.
- `any_htn_med`:
 - Tagged NA "a": Valid skip.
 - Tagged NA "b": Don't know, refusal, or not stated.
- `ccc_32`, `cvd_status`, `diab_status`, `ckd_status`:
 - `6`: Valid skip. Handled as `haven::tagged_na("a")`.
 - `7-9`: Don't know, refusal, or not stated. Handled as `haven::tagged_na("b")`.

```

## Value

**integer** The hypertension status:

- 1: Hypertension controlled (BP < 140/90 mmHg (or < 130/80 mmHg if diabetes or CKD) when on hypertension medication)
- 2: Hypertension not controlled (BP >= 140/90 mmHg (or >= 130/80 mmHg if diabetes or CKD) when on hypertension medication)
- haven::tagged\_na("a"): Not applicable
- haven::tagged\_na("b"): Missing

**See Also**

[derive\\_hypertension\\_control\(\)](#) for controlled status with unadjusted BP

**Examples**

```
Scalar usage: Single respondent
Example 1: Respondent has adjusted SBP = 150, adjusted DBP = 95, and on medication.
derive_hypertension_control_adj(sbp_adj_mmhg = 150, dbp_adj_mmhg = 95, any_htn_med = 1)
Output: 2 (Hypertension not controlled due to high adjusted SBP and DBP despite medication usage).

Example 2: Respondent has adjusted SBP = 120, adjusted DBP = 80, and on medication.
derive_hypertension_control_adj(sbp_adj_mmhg = 120, dbp_adj_mmhg = 80, any_htn_med = 1)
Output: 1 (Hypertension controlled as adjusted BP is below 140/90 mmHg and on medication).

Example 3: Respondent has non-response BP values of 996 for both systolic and diastolic.
result <- derive_hypertension_control_adj(sbp_adj_mmhg = 996, dbp_adj_mmhg = 996, any_htn_med = 0)
result # Shows: NA
haven::is_tagged_na(result, "a") # Shows: TRUE (confirms it's tagged NA(a))
format(result, tag = TRUE) # Shows: "NA(a)" (displays the tag)

Multiple respondents
derive_hypertension_control_adj(
 sbp_adj_mmhg = c(150, 120, 135), dbp_adj_mmhg = c(95, 80, 85),
 any_htn_med = c(1, 1, 1), diab_status = c(2, 2, 1)
)
Returns: c(2, 1, 2)

Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
 mutate(sbp_adj_mmhg = adjust_sbp(bpmdpbps), dbp_adj_mmhg = adjust_dbp(bpmdpdpd)) |>
 mutate(any_htn_med = 1) |>
 mutate(ctrl_adj = derive_hypertension_control_adj(sbp_adj_mmhg, dbp_adj_mmhg, any_htn_med)) |>
 select(clinid, sbp_adj_mmhg, dbp_adj_mmhg, ctrl_adj) |>
 head()
```

---

is\_ace\_inhibitor

*ACE inhibitors*

---

**Description**

This function checks if a given medication is an ACE inhibitor. This function processes multiple inputs efficiently.

**Usage**

```
is_ace_inhibitor(meucatc, npi_25b)
```

**Arguments**

meucatc **character** ATC code of the medication.  
 npi\_25b **integer** Time when the medication was last taken.

**Details**

Identifies ACE inhibitors based on ATC codes starting with "C09".

```

Missing Data Codes:
- `meucatc`: `9999996` (Not applicable), `9999997-9999999` (Missing)
- `npi_25b`: `6` (Not applicable), `7-9` (Missing)

```

**Value**

**numeric** 1 if medication is an ACE inhibitor, 0 otherwise. If inputs are invalid or out of bounds, the function returns a tagged NA.

**Examples**

```

Scalar usage: Single respondent
is_ace_inhibitor("C09AB03", 2)
Returns: 1

Example: Respondent has non-response values for all inputs.
result <- is_ace_inhibitor("9999998", 8)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

Multiple respondents
is_ace_inhibitor(c("C09AB03", "C01AA05"), c(2, 1))
Returns: c(1, 0)

Database usage: Applied to survey datasets
library(dplyr)
cycle3_meds |>
 mutate(ace_inhibitor = is_ace_inhibitor(meucatc, npi_25b)) |>
 head()

```

---

is\_ace\_med\_cycles1to2 *ACE inhibitors - cycles 1-2*

---

**Description**

This function checks if a person is taking ACE inhibitors based on the provided Anatomical Therapeutic Chemical (ATC) codes for medications and the Canadian Health Measures Survey (CHMS) response for the time when the medication was last taken.

**Usage**

```
is_ace_med_cycles1to2(
 atc_101a = NULL,
 atc_102a = NULL,
 atc_103a = NULL,
 atc_104a = NULL,
 atc_105a = NULL,
 atc_106a = NULL,
 atc_107a = NULL,
 atc_108a = NULL,
 atc_109a = NULL,
 atc_110a = NULL,
 atc_111a = NULL,
 atc_112a = NULL,
 atc_113a = NULL,
 atc_114a = NULL,
 atc_115a = NULL,
 atc_201a = NULL,
 atc_202a = NULL,
 atc_203a = NULL,
 atc_204a = NULL,
 atc_205a = NULL,
 atc_206a = NULL,
 atc_207a = NULL,
 atc_208a = NULL,
 atc_209a = NULL,
 atc_210a = NULL,
 atc_211a = NULL,
 atc_212a = NULL,
 atc_213a = NULL,
 atc_214a = NULL,
 atc_215a = NULL,
 atc_131a = NULL,
 atc_132a = NULL,
 atc_133a = NULL,
 atc_134a = NULL,
 atc_135a = NULL,
 atc_231a = NULL,
 atc_232a = NULL,
 atc_233a = NULL,
 atc_234a = NULL,
 atc_235a = NULL,
 mhr_101b = NULL,
 mhr_102b = NULL,
 mhr_103b = NULL,
 mhr_104b = NULL,
 mhr_105b = NULL,
 mhr_106b = NULL,
)
```

```
mhr_107b = NULL,
mhr_108b = NULL,
mhr_109b = NULL,
mhr_110b = NULL,
mhr_111b = NULL,
mhr_112b = NULL,
mhr_113b = NULL,
mhr_114b = NULL,
mhr_115b = NULL,
mhr_201b = NULL,
mhr_202b = NULL,
mhr_203b = NULL,
mhr_204b = NULL,
mhr_205b = NULL,
mhr_206b = NULL,
mhr_207b = NULL,
mhr_208b = NULL,
mhr_209b = NULL,
mhr_210b = NULL,
mhr_211b = NULL,
mhr_212b = NULL,
mhr_213b = NULL,
mhr_214b = NULL,
mhr_215b = NULL,
mhr_131b = NULL,
mhr_132b = NULL,
mhr_133b = NULL,
mhr_134b = NULL,
mhr_135b = NULL,
mhr_231b = NULL,
mhr_232b = NULL,
mhr_233b = NULL,
mhr_234b = NULL,
mhr_235b = NULL
)
```

### Arguments

|          |                                                                                     |
|----------|-------------------------------------------------------------------------------------|
| atc_101a | <a href="#">character</a> ATC code of respondent's first prescription medication.   |
| atc_102a | <a href="#">character</a> ATC code of respondent's second prescription medication.  |
| atc_103a | <a href="#">character</a> ATC code of respondent's third prescription medication.   |
| atc_104a | <a href="#">character</a> ATC code of respondent's fourth prescription medication.  |
| atc_105a | <a href="#">character</a> ATC code of respondent's fifth prescription medication.   |
| atc_106a | <a href="#">character</a> ATC code of respondent's sixth prescription medication.   |
| atc_107a | <a href="#">character</a> ATC code of respondent's seventh prescription medication. |
| atc_108a | <a href="#">character</a> ATC code of respondent's eighth prescription medication.  |

|          |           |                                                                                                 |
|----------|-----------|-------------------------------------------------------------------------------------------------|
| atc_109a | character | ATC code of respondent's ninth prescription medication.                                         |
| atc_110a | character | ATC code of respondent's tenth prescription medication.                                         |
| atc_111a | character | ATC code of respondent's eleventh prescription medication.                                      |
| atc_112a | character | ATC code of respondent's twelfth prescription medication.                                       |
| atc_113a | character | ATC code of respondent's thirteenth prescription medication.                                    |
| atc_114a | character | ATC code of respondent's fourteenth prescription medication.                                    |
| atc_115a | character | ATC code of respondent's fifteenth prescription medication.                                     |
| atc_201a | character | ATC code of respondent's first over-the-counter medication.                                     |
| atc_202a | character | ATC code of respondent's second over-the-counter medication.                                    |
| atc_203a | character | ATC code of respondent's third over-the-counter medication.                                     |
| atc_204a | character | ATC code of respondent's fourth over-the-counter medication.                                    |
| atc_205a | character | ATC code of respondent's fifth over-the-counter medication.                                     |
| atc_206a | character | ATC code of respondent's sixth over-the-counter medication.                                     |
| atc_207a | character | ATC code of respondent's seventh over-the-counter medication.                                   |
| atc_208a | character | ATC code of respondent's eighth over-the-counter medication.                                    |
| atc_209a | character | ATC code of respondent's ninth over-the-counter medication.                                     |
| atc_210a | character | ATC code of respondent's tenth over-the-counter medication.                                     |
| atc_211a | character | ATC code of respondent's eleventh over-the-counter medication.                                  |
| atc_212a | character | ATC code of respondent's twelfth over-the-counter medication.                                   |
| atc_213a | character | ATC code of respondent's thirteenth over-the-counter medication.                                |
| atc_214a | character | ATC code of respondent's fourteenth over-the-counter medication.                                |
| atc_215a | character | ATC code of respondent's fifteenth over-the-counter medication.                                 |
| atc_131a | character | ATC code of respondent's first new prescription medication.                                     |
| atc_132a | character | ATC code of respondent's second new prescription medication.                                    |
| atc_133a | character | ATC code of respondent's third new prescription medication.                                     |
| atc_134a | character | ATC code of respondent's fourth new prescription medication.                                    |
| atc_135a | character | ATC code of respondent's fifth new prescription medication.                                     |
| atc_231a | character | ATC code of respondent's first new over-the-counter medication.                                 |
| atc_232a | character | ATC code of respondent's second new over-the-counter medication.                                |
| atc_233a | character | ATC code of respondent's third new over-the-counter medication.                                 |
| atc_234a | character | ATC code of respondent's fourth new over-the-counter medication.                                |
| atc_235a | character | ATC code of respondent's fifth new over-the-counter medication.                                 |
| mhr_101b | integer   | Response for when the first prescription medication was last taken (1 = Today, ..., 6 = Never). |
| mhr_102b | integer   | Response for when the second prescription medication was last taken (1-6).                      |
| mhr_103b | integer   | Response for when the third prescription medication was last taken (1-6).                       |

|          |                                                                                                         |
|----------|---------------------------------------------------------------------------------------------------------|
| mhr_104b | <a href="#">integer</a> Response for when the fourth prescription medication was last taken (1-6).      |
| mhr_105b | <a href="#">integer</a> Response for when the fifth prescription medication was last taken (1-6).       |
| mhr_106b | <a href="#">integer</a> Response for when the sixth prescription medication was last taken (1-6).       |
| mhr_107b | <a href="#">integer</a> Response for when the seventh prescription medication was last taken (1-6).     |
| mhr_108b | <a href="#">integer</a> Response for when the eighth prescription medication was last taken (1-6).      |
| mhr_109b | <a href="#">integer</a> Response for when the ninth prescription medication was last taken (1-6).       |
| mhr_110b | <a href="#">integer</a> Response for when the tenth prescription medication was last taken (1-6).       |
| mhr_111b | <a href="#">integer</a> Response for when the eleventh prescription medication was last taken (1-6).    |
| mhr_112b | <a href="#">integer</a> Response for when the twelfth prescription medication was last taken (1-6).     |
| mhr_113b | <a href="#">integer</a> Response for when the thirteenth prescription medication was last taken (1-6).  |
| mhr_114b | <a href="#">integer</a> Response for when the fourteenth prescription medication was last taken (1-6).  |
| mhr_115b | <a href="#">integer</a> Response for when the fifteenth prescription medication was last taken (1-6).   |
| mhr_201b | <a href="#">integer</a> Response for when the first over-the-counter medication was last taken (1-6).   |
| mhr_202b | <a href="#">integer</a> Response for when the second over-the-counter medication was last taken (1-6).  |
| mhr_203b | <a href="#">integer</a> Response for when the third over-the-counter medication was last taken (1-6).   |
| mhr_204b | <a href="#">integer</a> Response for when the fourth over-the-counter medication was last taken (1-6).  |
| mhr_205b | <a href="#">integer</a> Response for when the fifth over-the-counter medication was last taken (1-6).   |
| mhr_206b | <a href="#">integer</a> Response for when the sixth over-the-counter medication was last taken (1-6).   |
| mhr_207b | <a href="#">integer</a> Response for when the seventh over-the-counter medication was last taken (1-6). |
| mhr_208b | <a href="#">integer</a> Response for when the eighth over-the-counter medication was last taken (1-6).  |
| mhr_209b | <a href="#">integer</a> Response for when the ninth over-the-counter medication was last taken (1-6).   |
| mhr_210b | <a href="#">integer</a> Response for when the tenth over-the-counter medication was last taken (1-6).   |

|          |                                                                                                   |
|----------|---------------------------------------------------------------------------------------------------|
| mhr_211b | <b>integer</b> Response for when the eleventh over-the-counter medication was last taken (1-6).   |
| mhr_212b | <b>integer</b> Response for when the twelfth over-the-counter medication was last taken (1-6).    |
| mhr_213b | <b>integer</b> Response for when the thirteenth over-the-counter medication was last taken (1-6). |
| mhr_214b | <b>integer</b> Response for when the fourteenth over-the-counter medication was last taken (1-6). |
| mhr_215b | <b>integer</b> Response for when the fifteenth over-the-counter medication was last taken (1-6).  |
| mhr_131b | <b>integer</b> Response for when the first new prescription medication was last taken (1-6).      |
| mhr_132b | <b>integer</b> Response for when the second new prescription medication was last taken (1-6).     |
| mhr_133b | <b>integer</b> Response for when the third new prescription medication was last taken (1-6).      |
| mhr_134b | <b>integer</b> Response for when the fourth new prescription medication was last taken (1-6).     |
| mhr_135b | <b>integer</b> Response for when the fifth new prescription medication was last taken (1-6).      |
| mhr_231b | <b>integer</b> Response for when the first new over-the-counter medication was last taken (1-6).  |
| mhr_232b | <b>integer</b> Response for when the second new over-the-counter medication was last taken (1-6). |
| mhr_233b | <b>integer</b> Response for when the third new over-the-counter medication was last taken (1-6).  |
| mhr_234b | <b>integer</b> Response for when the fourth new over-the-counter medication was last taken (1-6). |
| mhr_235b | <b>integer</b> Response for when the fifth new over-the-counter medication was last taken (1-6).  |

### Details

The function identifies ACE inhibitors based on ATC codes starting with "C09". It checks all medication variables provided in the input data frame.

**\*\*Missing Data Codes:\*\***

- The function handles tagged NAs from the ``is_ace_inhibitor`` function and propagates them.

### Value

**numeric** Returns 1 if the person is taking ACE inhibitors, 0 otherwise. If all medication information is missing, it returns a tagged NA.

**See Also**

is\_ace\_inhibitor

**Examples**

```
This is a wrapper function and is not intended to be called directly by the user.
See `is_ace_inhibitor` for usage examples.
```

---

is\_any\_antihtn\_med      *Any anti-hypertensive medications*

---

**Description**

This function checks if a given medication is any anti-hypertensive drug. This function processes multiple inputs efficiently.

**Usage**

```
is_any_antihtn_med(meucatc, npi_25b)
```

**Arguments**

meucatc            **character** ATC code of the medication.  
npi\_25b            **integer** Time when the medication was last taken.

**Details**

Identifies anti-hypertensive drugs based on ATC codes starting with "C02", "C03", "C07", "C08", or "C09", excluding specific sub-codes.

```
Missing Data Codes:
- `meucatc`: `9999996` (Not applicable), `9999997-9999999` (Missing)
- `npi_25b`: `6` (Not applicable), `7-9` (Missing)
```

**Value**

**numeric** 1 if medication is an anti-hypertensive drug, 0 otherwise. If inputs are invalid or out of bounds, the function returns a tagged NA.

**Examples**

```
Scalar usage: Single respondent
is_any_antihtn_med("C07AB02", 4)
Returns: 1

Example: Respondent has non-response values for all inputs.
result <- is_any_antihtn_med("9999998", 8)
result # Shows: NA
```

```

haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

Multiple respondents
is_any_antihtn_med(c("C07AB02", "C07AA07"), c(4, 2))
Returns: c(1, 0)

Database usage: Applied to survey datasets
library(dplyr)
cycle3_meds |>
 mutate(any_antihtn = is_any_antihtn_med(meucatc, npi_25b)) |>
 head()

```

---

is\_any\_htn\_med\_cycles1to2

*Any anti-hypertensive medications - cycles 1-2*

---

### Description

This function checks if a person is taking any anti-hypertensive medication based on the provided Anatomical Therapeutic Chemical (ATC) codes for medications and the Canadian Health Measures Survey (CHMS) response for the time when the medication was last taken.

### Usage

```

is_any_htn_med_cycles1to2(
 atc_101a = NULL,
 atc_102a = NULL,
 atc_103a = NULL,
 atc_104a = NULL,
 atc_105a = NULL,
 atc_106a = NULL,
 atc_107a = NULL,
 atc_108a = NULL,
 atc_109a = NULL,
 atc_110a = NULL,
 atc_111a = NULL,
 atc_112a = NULL,
 atc_113a = NULL,
 atc_114a = NULL,
 atc_115a = NULL,
 atc_201a = NULL,
 atc_202a = NULL,
 atc_203a = NULL,
 atc_204a = NULL,
 atc_205a = NULL,
 atc_206a = NULL,

```

atc\_207a = NULL,  
atc\_208a = NULL,  
atc\_209a = NULL,  
atc\_210a = NULL,  
atc\_211a = NULL,  
atc\_212a = NULL,  
atc\_213a = NULL,  
atc\_214a = NULL,  
atc\_215a = NULL,  
atc\_131a = NULL,  
atc\_132a = NULL,  
atc\_133a = NULL,  
atc\_134a = NULL,  
atc\_135a = NULL,  
atc\_231a = NULL,  
atc\_232a = NULL,  
atc\_233a = NULL,  
atc\_234a = NULL,  
atc\_235a = NULL,  
mhr\_101b = NULL,  
mhr\_102b = NULL,  
mhr\_103b = NULL,  
mhr\_104b = NULL,  
mhr\_105b = NULL,  
mhr\_106b = NULL,  
mhr\_107b = NULL,  
mhr\_108b = NULL,  
mhr\_109b = NULL,  
mhr\_110b = NULL,  
mhr\_111b = NULL,  
mhr\_112b = NULL,  
mhr\_113b = NULL,  
mhr\_114b = NULL,  
mhr\_115b = NULL,  
mhr\_201b = NULL,  
mhr\_202b = NULL,  
mhr\_203b = NULL,  
mhr\_204b = NULL,  
mhr\_205b = NULL,  
mhr\_206b = NULL,  
mhr\_207b = NULL,  
mhr\_208b = NULL,  
mhr\_209b = NULL,  
mhr\_210b = NULL,  
mhr\_211b = NULL,  
mhr\_212b = NULL,  
mhr\_213b = NULL,  
mhr\_214b = NULL,

```
mhr_215b = NULL,
mhr_131b = NULL,
mhr_132b = NULL,
mhr_133b = NULL,
mhr_134b = NULL,
mhr_135b = NULL,
mhr_231b = NULL,
mhr_232b = NULL,
mhr_233b = NULL,
mhr_234b = NULL,
mhr_235b = NULL
)
```

### Arguments

|          |                                                                                          |
|----------|------------------------------------------------------------------------------------------|
| atc_101a | <a href="#">character</a> ATC code of respondent's first prescription medication.        |
| atc_102a | <a href="#">character</a> ATC code of respondent's second prescription medication.       |
| atc_103a | <a href="#">character</a> ATC code of respondent's third prescription medication.        |
| atc_104a | <a href="#">character</a> ATC code of respondent's fourth prescription medication.       |
| atc_105a | <a href="#">character</a> ATC code of respondent's fifth prescription medication.        |
| atc_106a | <a href="#">character</a> ATC code of respondent's sixth prescription medication.        |
| atc_107a | <a href="#">character</a> ATC code of respondent's seventh prescription medication.      |
| atc_108a | <a href="#">character</a> ATC code of respondent's eighth prescription medication.       |
| atc_109a | <a href="#">character</a> ATC code of respondent's ninth prescription medication.        |
| atc_110a | <a href="#">character</a> ATC code of respondent's tenth prescription medication.        |
| atc_111a | <a href="#">character</a> ATC code of respondent's eleventh prescription medication.     |
| atc_112a | <a href="#">character</a> ATC code of respondent's twelfth prescription medication.      |
| atc_113a | <a href="#">character</a> ATC code of respondent's thirteenth prescription medication.   |
| atc_114a | <a href="#">character</a> ATC code of respondent's fourteenth prescription medication.   |
| atc_115a | <a href="#">character</a> ATC code of respondent's fifteenth prescription medication.    |
| atc_201a | <a href="#">character</a> ATC code of respondent's first over-the-counter medication.    |
| atc_202a | <a href="#">character</a> ATC code of respondent's second over-the-counter medication.   |
| atc_203a | <a href="#">character</a> ATC code of respondent's third over-the-counter medication.    |
| atc_204a | <a href="#">character</a> ATC code of respondent's fourth over-the-counter medication.   |
| atc_205a | <a href="#">character</a> ATC code of respondent's fifth over-the-counter medication.    |
| atc_206a | <a href="#">character</a> ATC code of respondent's sixth over-the-counter medication.    |
| atc_207a | <a href="#">character</a> ATC code of respondent's seventh over-the-counter medication.  |
| atc_208a | <a href="#">character</a> ATC code of respondent's eighth over-the-counter medication.   |
| atc_209a | <a href="#">character</a> ATC code of respondent's ninth over-the-counter medication.    |
| atc_210a | <a href="#">character</a> ATC code of respondent's tenth over-the-counter medication.    |
| atc_211a | <a href="#">character</a> ATC code of respondent's eleventh over-the-counter medication. |

|          |           |                                                                                                    |
|----------|-----------|----------------------------------------------------------------------------------------------------|
| atc_212a | character | ATC code of respondent's twelfth over-the-counter medication.                                      |
| atc_213a | character | ATC code of respondent's thirteenth over-the-counter medication.                                   |
| atc_214a | character | ATC code of respondent's fourteenth over-the-counter medication.                                   |
| atc_215a | character | ATC code of respondent's fifteenth over-the-counter medication.                                    |
| atc_131a | character | ATC code of respondent's first new prescription medication.                                        |
| atc_132a | character | ATC code of respondent's second new prescription medication.                                       |
| atc_133a | character | ATC code of respondent's third new prescription medication.                                        |
| atc_134a | character | ATC code of respondent's fourth new prescription medication.                                       |
| atc_135a | character | ATC code of respondent's fifth new prescription medication.                                        |
| atc_231a | character | ATC code of respondent's first new over-the-counter medication.                                    |
| atc_232a | character | ATC code of respondent's second new over-the-counter medication.                                   |
| atc_233a | character | ATC code of respondent's third new over-the-counter medication.                                    |
| atc_234a | character | ATC code of respondent's fourth new over-the-counter medication.                                   |
| atc_235a | character | ATC code of respondent's fifth new over-the-counter medication.                                    |
| mhr_101b | integer   | Response for when the first prescription medication was last taken (1 = Today, . . . , 6 = Never). |
| mhr_102b | integer   | Response for when the second prescription medication was last taken (1-6).                         |
| mhr_103b | integer   | Response for when the third prescription medication was last taken (1-6).                          |
| mhr_104b | integer   | Response for when the fourth prescription medication was last taken (1-6).                         |
| mhr_105b | integer   | Response for when the fifth prescription medication was last taken (1-6).                          |
| mhr_106b | integer   | Response for when the sixth prescription medication was last taken (1-6).                          |
| mhr_107b | integer   | Response for when the seventh prescription medication was last taken (1-6).                        |
| mhr_108b | integer   | Response for when the eighth prescription medication was last taken (1-6).                         |
| mhr_109b | integer   | Response for when the ninth prescription medication was last taken (1-6).                          |
| mhr_110b | integer   | Response for when the tenth prescription medication was last taken (1-6).                          |
| mhr_111b | integer   | Response for when the eleventh prescription medication was last taken (1-6).                       |
| mhr_112b | integer   | Response for when the twelfth prescription medication was last taken (1-6).                        |
| mhr_113b | integer   | Response for when the thirteenth prescription medication was last taken (1-6).                     |
| mhr_114b | integer   | Response for when the fourteenth prescription medication was last taken (1-6).                     |

|          |                                                                                                   |
|----------|---------------------------------------------------------------------------------------------------|
| mhr_115b | <b>integer</b> Response for when the fifteenth prescription medication was last taken (1-6).      |
| mhr_201b | <b>integer</b> Response for when the first over-the-counter medication was last taken (1-6).      |
| mhr_202b | <b>integer</b> Response for when the second over-the-counter medication was last taken (1-6).     |
| mhr_203b | <b>integer</b> Response for when the third over-the-counter medication was last taken (1-6).      |
| mhr_204b | <b>integer</b> Response for when the fourth over-the-counter medication was last taken (1-6).     |
| mhr_205b | <b>integer</b> Response for when the fifth over-the-counter medication was last taken (1-6).      |
| mhr_206b | <b>integer</b> Response for when the sixth over-the-counter medication was last taken (1-6).      |
| mhr_207b | <b>integer</b> Response for when the seventh over-the-counter medication was last taken (1-6).    |
| mhr_208b | <b>integer</b> Response for when the eighth over-the-counter medication was last taken (1-6).     |
| mhr_209b | <b>integer</b> Response for when the ninth over-the-counter medication was last taken (1-6).      |
| mhr_210b | <b>integer</b> Response for when the tenth over-the-counter medication was last taken (1-6).      |
| mhr_211b | <b>integer</b> Response for when the eleventh over-the-counter medication was last taken (1-6).   |
| mhr_212b | <b>integer</b> Response for when the twelfth over-the-counter medication was last taken (1-6).    |
| mhr_213b | <b>integer</b> Response for when the thirteenth over-the-counter medication was last taken (1-6). |
| mhr_214b | <b>integer</b> Response for when the fourteenth over-the-counter medication was last taken (1-6). |
| mhr_215b | <b>integer</b> Response for when the fifteenth over-the-counter medication was last taken (1-6).  |
| mhr_131b | <b>integer</b> Response for when the first new prescription medication was last taken (1-6).      |
| mhr_132b | <b>integer</b> Response for when the second new prescription medication was last taken (1-6).     |
| mhr_133b | <b>integer</b> Response for when the third new prescription medication was last taken (1-6).      |
| mhr_134b | <b>integer</b> Response for when the fourth new prescription medication was last taken (1-6).     |
| mhr_135b | <b>integer</b> Response for when the fifth new prescription medication was last taken (1-6).      |

|          |                                                                                                   |
|----------|---------------------------------------------------------------------------------------------------|
| mhr_231b | <b>integer</b> Response for when the first new over-the-counter medication was last taken (1-6).  |
| mhr_232b | <b>integer</b> Response for when the second new over-the-counter medication was last taken (1-6). |
| mhr_233b | <b>integer</b> Response for when the third new over-the-counter medication was last taken (1-6).  |
| mhr_234b | <b>integer</b> Response for when the fourth new over-the-counter medication was last taken (1-6). |
| mhr_235b | <b>integer</b> Response for when the fifth new over-the-counter medication was last taken (1-6).  |

### Details

The function identifies anti-hypertensive drugs based on ATC codes starting with "C02", "C03", "C07", "C08", or "C09", excluding specific sub-codes. It checks all medication variables provided in the input data frame.

**\*\*Missing Data Codes:\*\***  
 - The function handles tagged NAs from the ``is_any_antihtn_med`` function and propagates them.

### Value

**numeric** Returns 1 if the person is taking any anti-hypertensive medication, 0 otherwise. If all medication information is missing, it returns a tagged NA.

### See Also

`is_any_antihtn_med`

### Examples

```
This is a wrapper function and is not intended to be called directly by the user.
See `is_any_antihtn_med` for usage examples.
```

---

is\_bb\_med\_cycles1to2 *Beta blockers - cycles 1-2*

---

### Description

This function checks if a person is taking beta blockers based on the provided Anatomical Therapeutic Chemical (ATC) codes for medications and the Canadian Health Measures Survey (CHMS) response for the time when the medication was last taken.

**Usage**

```
is_bb_med_cycles1to2(
 atc_101a = NULL,
 atc_102a = NULL,
 atc_103a = NULL,
 atc_104a = NULL,
 atc_105a = NULL,
 atc_106a = NULL,
 atc_107a = NULL,
 atc_108a = NULL,
 atc_109a = NULL,
 atc_110a = NULL,
 atc_111a = NULL,
 atc_112a = NULL,
 atc_113a = NULL,
 atc_114a = NULL,
 atc_115a = NULL,
 atc_201a = NULL,
 atc_202a = NULL,
 atc_203a = NULL,
 atc_204a = NULL,
 atc_205a = NULL,
 atc_206a = NULL,
 atc_207a = NULL,
 atc_208a = NULL,
 atc_209a = NULL,
 atc_210a = NULL,
 atc_211a = NULL,
 atc_212a = NULL,
 atc_213a = NULL,
 atc_214a = NULL,
 atc_215a = NULL,
 atc_131a = NULL,
 atc_132a = NULL,
 atc_133a = NULL,
 atc_134a = NULL,
 atc_135a = NULL,
 atc_231a = NULL,
 atc_232a = NULL,
 atc_233a = NULL,
 atc_234a = NULL,
 atc_235a = NULL,
 mhr_101b = NULL,
 mhr_102b = NULL,
 mhr_103b = NULL,
 mhr_104b = NULL,
 mhr_105b = NULL,
 mhr_106b = NULL,
)
```

```
mhr_107b = NULL,
mhr_108b = NULL,
mhr_109b = NULL,
mhr_110b = NULL,
mhr_111b = NULL,
mhr_112b = NULL,
mhr_113b = NULL,
mhr_114b = NULL,
mhr_115b = NULL,
mhr_201b = NULL,
mhr_202b = NULL,
mhr_203b = NULL,
mhr_204b = NULL,
mhr_205b = NULL,
mhr_206b = NULL,
mhr_207b = NULL,
mhr_208b = NULL,
mhr_209b = NULL,
mhr_210b = NULL,
mhr_211b = NULL,
mhr_212b = NULL,
mhr_213b = NULL,
mhr_214b = NULL,
mhr_215b = NULL,
mhr_131b = NULL,
mhr_132b = NULL,
mhr_133b = NULL,
mhr_134b = NULL,
mhr_135b = NULL,
mhr_231b = NULL,
mhr_232b = NULL,
mhr_233b = NULL,
mhr_234b = NULL,
mhr_235b = NULL
)
```

### Arguments

|          |                                                                                     |
|----------|-------------------------------------------------------------------------------------|
| atc_101a | <a href="#">character</a> ATC code of respondent's first prescription medication.   |
| atc_102a | <a href="#">character</a> ATC code of respondent's second prescription medication.  |
| atc_103a | <a href="#">character</a> ATC code of respondent's third prescription medication.   |
| atc_104a | <a href="#">character</a> ATC code of respondent's fourth prescription medication.  |
| atc_105a | <a href="#">character</a> ATC code of respondent's fifth prescription medication.   |
| atc_106a | <a href="#">character</a> ATC code of respondent's sixth prescription medication.   |
| atc_107a | <a href="#">character</a> ATC code of respondent's seventh prescription medication. |
| atc_108a | <a href="#">character</a> ATC code of respondent's eighth prescription medication.  |

|          |           |                                                                                                    |
|----------|-----------|----------------------------------------------------------------------------------------------------|
| atc_109a | character | ATC code of respondent's ninth prescription medication.                                            |
| atc_110a | character | ATC code of respondent's tenth prescription medication.                                            |
| atc_111a | character | ATC code of respondent's eleventh prescription medication.                                         |
| atc_112a | character | ATC code of respondent's twelfth prescription medication.                                          |
| atc_113a | character | ATC code of respondent's thirteenth prescription medication.                                       |
| atc_114a | character | ATC code of respondent's fourteenth prescription medication.                                       |
| atc_115a | character | ATC code of respondent's fifteenth prescription medication.                                        |
| atc_201a | character | ATC code of respondent's first over-the-counter medication.                                        |
| atc_202a | character | ATC code of respondent's second over-the-counter medication.                                       |
| atc_203a | character | ATC code of respondent's third over-the-counter medication.                                        |
| atc_204a | character | ATC code of respondent's fourth over-the-counter medication.                                       |
| atc_205a | character | ATC code of respondent's fifth over-the-counter medication.                                        |
| atc_206a | character | ATC code of respondent's sixth over-the-counter medication.                                        |
| atc_207a | character | ATC code of respondent's seventh over-the-counter medication.                                      |
| atc_208a | character | ATC code of respondent's eighth over-the-counter medication.                                       |
| atc_209a | character | ATC code of respondent's ninth over-the-counter medication.                                        |
| atc_210a | character | ATC code of respondent's tenth over-the-counter medication.                                        |
| atc_211a | character | ATC code of respondent's eleventh over-the-counter medication.                                     |
| atc_212a | character | ATC code of respondent's twelfth over-the-counter medication.                                      |
| atc_213a | character | ATC code of respondent's thirteenth over-the-counter medication.                                   |
| atc_214a | character | ATC code of respondent's fourteenth over-the-counter medication.                                   |
| atc_215a | character | ATC code of respondent's fifteenth over-the-counter medication.                                    |
| atc_131a | character | ATC code of respondent's first new prescription medication.                                        |
| atc_132a | character | ATC code of respondent's second new prescription medication.                                       |
| atc_133a | character | ATC code of respondent's third new prescription medication.                                        |
| atc_134a | character | ATC code of respondent's fourth new prescription medication.                                       |
| atc_135a | character | ATC code of respondent's fifth new prescription medication.                                        |
| atc_231a | character | ATC code of respondent's first new over-the-counter medication.                                    |
| atc_232a | character | ATC code of respondent's second new over-the-counter medication.                                   |
| atc_233a | character | ATC code of respondent's third new over-the-counter medication.                                    |
| atc_234a | character | ATC code of respondent's fourth new over-the-counter medication.                                   |
| atc_235a | character | ATC code of respondent's fifth new over-the-counter medication.                                    |
| mhr_101b | integer   | Response for when the first prescription medication was last taken (1 = Today, . . . , 6 = Never). |
| mhr_102b | integer   | Response for when the second prescription medication was last taken (1-6).                         |
| mhr_103b | integer   | Response for when the third prescription medication was last taken (1-6).                          |

|          |                                                                                                         |
|----------|---------------------------------------------------------------------------------------------------------|
| mhr_104b | <a href="#">integer</a> Response for when the fourth prescription medication was last taken (1-6).      |
| mhr_105b | <a href="#">integer</a> Response for when the fifth prescription medication was last taken (1-6).       |
| mhr_106b | <a href="#">integer</a> Response for when the sixth prescription medication was last taken (1-6).       |
| mhr_107b | <a href="#">integer</a> Response for when the seventh prescription medication was last taken (1-6).     |
| mhr_108b | <a href="#">integer</a> Response for when the eighth prescription medication was last taken (1-6).      |
| mhr_109b | <a href="#">integer</a> Response for when the ninth prescription medication was last taken (1-6).       |
| mhr_110b | <a href="#">integer</a> Response for when the tenth prescription medication was last taken (1-6).       |
| mhr_111b | <a href="#">integer</a> Response for when the eleventh prescription medication was last taken (1-6).    |
| mhr_112b | <a href="#">integer</a> Response for when the twelfth prescription medication was last taken (1-6).     |
| mhr_113b | <a href="#">integer</a> Response for when the thirteenth prescription medication was last taken (1-6).  |
| mhr_114b | <a href="#">integer</a> Response for when the fourteenth prescription medication was last taken (1-6).  |
| mhr_115b | <a href="#">integer</a> Response for when the fifteenth prescription medication was last taken (1-6).   |
| mhr_201b | <a href="#">integer</a> Response for when the first over-the-counter medication was last taken (1-6).   |
| mhr_202b | <a href="#">integer</a> Response for when the second over-the-counter medication was last taken (1-6).  |
| mhr_203b | <a href="#">integer</a> Response for when the third over-the-counter medication was last taken (1-6).   |
| mhr_204b | <a href="#">integer</a> Response for when the fourth over-the-counter medication was last taken (1-6).  |
| mhr_205b | <a href="#">integer</a> Response for when the fifth over-the-counter medication was last taken (1-6).   |
| mhr_206b | <a href="#">integer</a> Response for when the sixth over-the-counter medication was last taken (1-6).   |
| mhr_207b | <a href="#">integer</a> Response for when the seventh over-the-counter medication was last taken (1-6). |
| mhr_208b | <a href="#">integer</a> Response for when the eighth over-the-counter medication was last taken (1-6).  |
| mhr_209b | <a href="#">integer</a> Response for when the ninth over-the-counter medication was last taken (1-6).   |
| mhr_210b | <a href="#">integer</a> Response for when the tenth over-the-counter medication was last taken (1-6).   |

|          |                                                                                                   |
|----------|---------------------------------------------------------------------------------------------------|
| mhr_211b | <b>integer</b> Response for when the eleventh over-the-counter medication was last taken (1-6).   |
| mhr_212b | <b>integer</b> Response for when the twelfth over-the-counter medication was last taken (1-6).    |
| mhr_213b | <b>integer</b> Response for when the thirteenth over-the-counter medication was last taken (1-6). |
| mhr_214b | <b>integer</b> Response for when the fourteenth over-the-counter medication was last taken (1-6). |
| mhr_215b | <b>integer</b> Response for when the fifteenth over-the-counter medication was last taken (1-6).  |
| mhr_131b | <b>integer</b> Response for when the first new prescription medication was last taken (1-6).      |
| mhr_132b | <b>integer</b> Response for when the second new prescription medication was last taken (1-6).     |
| mhr_133b | <b>integer</b> Response for when the third new prescription medication was last taken (1-6).      |
| mhr_134b | <b>integer</b> Response for when the fourth new prescription medication was last taken (1-6).     |
| mhr_135b | <b>integer</b> Response for when the fifth new prescription medication was last taken (1-6).      |
| mhr_231b | <b>integer</b> Response for when the first new over-the-counter medication was last taken (1-6).  |
| mhr_232b | <b>integer</b> Response for when the second new over-the-counter medication was last taken (1-6). |
| mhr_233b | <b>integer</b> Response for when the third new over-the-counter medication was last taken (1-6).  |
| mhr_234b | <b>integer</b> Response for when the fourth new over-the-counter medication was last taken (1-6). |
| mhr_235b | <b>integer</b> Response for when the fifth new over-the-counter medication was last taken (1-6).  |

### Details

The function identifies beta blockers based on ATC codes starting with "C07", excluding specific sub-codes. It checks all medication variables provided in the input data frame.

**\*\*Missing Data Codes:\*\***

- The function handles tagged NAs from the ``is_beta_blocker`` function and propagates them.

### Value

**numeric** Returns 1 if the respondent is taking beta blockers, 0 otherwise. If all medication information is missing, returns a tagged NA.

**See Also**

is\_beta\_blocker

**Examples**

```
This is a wrapper function and is not intended to be called directly by the user.
See `is_beta_blocker` for usage examples.
```

---

|                 |                      |
|-----------------|----------------------|
| is_beta_blocker | <i>Beta blockers</i> |
|-----------------|----------------------|

---

**Description**

This function determines whether a given medication is a beta blocker. This function processes multiple inputs efficiently.

**Usage**

```
is_beta_blocker(meucatc, npi_25b)
```

**Arguments**

meucatc            [character](#) ATC code of the medication.  
npi\_25b            [integer](#) Time when the medication was last taken.

**Details**

Identifies beta blockers based on ATC codes starting with "C07", excluding specific sub-codes.

```
Missing Data Codes:
- `meucatc`: `9999996` (Not applicable), `9999997-9999999` (Missing)
- `npi_25b`: `6` (Not applicable), `7-9` (Missing)
```

**Value**

[numeric](#) 1 if medication is a beta blocker, 0 otherwise. If inputs are invalid or out of bounds, the function returns a tagged NA.

**Examples**

```
Scalar usage: Single respondent
is_beta_blocker("C07AA13", 3)
Returns: 1

Example: Respondent has non-response values for all inputs.
result <- is_beta_blocker("9999998", 8)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
```

```
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

Multiple respondents
is_beta_blocker(c("C07AA13", "C07AA07"), c(3, 4))
Returns: c(1, 0)

Database usage: Applied to survey datasets
library(dplyr)
cycle3_meds |>
 mutate(beta_blocker = is_beta_blocker(meucatc, npi_25b)) |>
 head()
```

---

is\_calcium\_channel\_blocker

*Calcium channel blockers*

---

## Description

This function checks if a given medication is a calcium channel blocker. This function processes multiple inputs efficiently.

## Usage

```
is_calcium_channel_blocker(meucatc, npi_25b)
```

## Arguments

**meucatc** [character](#) ATC code of the medication.  
**npi\_25b** [integer](#) Time when the medication was last taken.

## Details

Identifies calcium channel blockers based on ATC codes starting with "C08".

```
Missing Data Codes:
- `meucatc`: `9999996` (Not applicable), `9999997-9999999` (Missing)
- `npi_25b`: `6` (Not applicable), `7-9` (Missing)
```

## Value

[numeric](#) 1 if medication is a calcium channel blocker, 0 otherwise. If inputs are invalid or out of bounds, the function returns a tagged NA.

**Examples**

```

Scalar usage: Single respondent
is_calcium_channel_blocker("C08CA05", 1)
Returns: 1

Example: Respondent has non-response values for all inputs.
result <- is_calcium_channel_blocker("9999998", 8)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

Multiple respondents
is_calcium_channel_blocker(c("C08CA05", "C01AA05"), c(1, 2))
Returns: c(1, 0)

Database usage: Applied to survey datasets
library(dplyr)
cycle3_meds |>
 mutate(ccb = is_calcium_channel_blocker(meucatc, npi_25b)) |>
 head()

```

---

is\_ccb\_med\_cycles1to2 *Calcium channel blockers - cycles 1-2*

---

**Description**

This function checks if a person is taking calcium channel blockers based on the provided Anatomical Therapeutic Chemical (ATC) codes for medications and the Canadian Health Measures Survey (CHMS) response for the time when the medication was last taken.

**Usage**

```

is_ccb_med_cycles1to2(
 atc_101a = NULL,
 atc_102a = NULL,
 atc_103a = NULL,
 atc_104a = NULL,
 atc_105a = NULL,
 atc_106a = NULL,
 atc_107a = NULL,
 atc_108a = NULL,
 atc_109a = NULL,
 atc_110a = NULL,
 atc_111a = NULL,
 atc_112a = NULL,
 atc_113a = NULL,
 atc_114a = NULL,

```

atc\_115a = NULL,  
atc\_201a = NULL,  
atc\_202a = NULL,  
atc\_203a = NULL,  
atc\_204a = NULL,  
atc\_205a = NULL,  
atc\_206a = NULL,  
atc\_207a = NULL,  
atc\_208a = NULL,  
atc\_209a = NULL,  
atc\_210a = NULL,  
atc\_211a = NULL,  
atc\_212a = NULL,  
atc\_213a = NULL,  
atc\_214a = NULL,  
atc\_215a = NULL,  
atc\_131a = NULL,  
atc\_132a = NULL,  
atc\_133a = NULL,  
atc\_134a = NULL,  
atc\_135a = NULL,  
atc\_231a = NULL,  
atc\_232a = NULL,  
atc\_233a = NULL,  
atc\_234a = NULL,  
atc\_235a = NULL,  
mhr\_101b = NULL,  
mhr\_102b = NULL,  
mhr\_103b = NULL,  
mhr\_104b = NULL,  
mhr\_105b = NULL,  
mhr\_106b = NULL,  
mhr\_107b = NULL,  
mhr\_108b = NULL,  
mhr\_109b = NULL,  
mhr\_110b = NULL,  
mhr\_111b = NULL,  
mhr\_112b = NULL,  
mhr\_113b = NULL,  
mhr\_114b = NULL,  
mhr\_115b = NULL,  
mhr\_201b = NULL,  
mhr\_202b = NULL,  
mhr\_203b = NULL,  
mhr\_204b = NULL,  
mhr\_205b = NULL,  
mhr\_206b = NULL,  
mhr\_207b = NULL,

```

mhr_208b = NULL,
mhr_209b = NULL,
mhr_210b = NULL,
mhr_211b = NULL,
mhr_212b = NULL,
mhr_213b = NULL,
mhr_214b = NULL,
mhr_215b = NULL,
mhr_131b = NULL,
mhr_132b = NULL,
mhr_133b = NULL,
mhr_134b = NULL,
mhr_135b = NULL,
mhr_231b = NULL,
mhr_232b = NULL,
mhr_233b = NULL,
mhr_234b = NULL,
mhr_235b = NULL
)

```

### Arguments

|          |                                                                               |
|----------|-------------------------------------------------------------------------------|
| atc_101a | <b>character</b> ATC code of respondent's first prescription medication.      |
| atc_102a | <b>character</b> ATC code of respondent's second prescription medication.     |
| atc_103a | <b>character</b> ATC code of respondent's third prescription medication.      |
| atc_104a | <b>character</b> ATC code of respondent's fourth prescription medication.     |
| atc_105a | <b>character</b> ATC code of respondent's fifth prescription medication.      |
| atc_106a | <b>character</b> ATC code of respondent's sixth prescription medication.      |
| atc_107a | <b>character</b> ATC code of respondent's seventh prescription medication.    |
| atc_108a | <b>character</b> ATC code of respondent's eighth prescription medication.     |
| atc_109a | <b>character</b> ATC code of respondent's ninth prescription medication.      |
| atc_110a | <b>character</b> ATC code of respondent's tenth prescription medication.      |
| atc_111a | <b>character</b> ATC code of respondent's eleventh prescription medication.   |
| atc_112a | <b>character</b> ATC code of respondent's twelfth prescription medication.    |
| atc_113a | <b>character</b> ATC code of respondent's thirteenth prescription medication. |
| atc_114a | <b>character</b> ATC code of respondent's fourteenth prescription medication. |
| atc_115a | <b>character</b> ATC code of respondent's fifteenth prescription medication.  |
| atc_201a | <b>character</b> ATC code of respondent's first over-the-counter medication.  |
| atc_202a | <b>character</b> ATC code of respondent's second over-the-counter medication. |
| atc_203a | <b>character</b> ATC code of respondent's third over-the-counter medication.  |
| atc_204a | <b>character</b> ATC code of respondent's fourth over-the-counter medication. |
| atc_205a | <b>character</b> ATC code of respondent's fifth over-the-counter medication.  |
| atc_206a | <b>character</b> ATC code of respondent's sixth over-the-counter medication.  |

|          |           |                                                                                                    |
|----------|-----------|----------------------------------------------------------------------------------------------------|
| atc_207a | character | ATC code of respondent's seventh over-the-counter medication.                                      |
| atc_208a | character | ATC code of respondent's eighth over-the-counter medication.                                       |
| atc_209a | character | ATC code of respondent's ninth over-the-counter medication.                                        |
| atc_210a | character | ATC code of respondent's tenth over-the-counter medication.                                        |
| atc_211a | character | ATC code of respondent's eleventh over-the-counter medication.                                     |
| atc_212a | character | ATC code of respondent's twelfth over-the-counter medication.                                      |
| atc_213a | character | ATC code of respondent's thirteenth over-the-counter medication.                                   |
| atc_214a | character | ATC code of respondent's fourteenth over-the-counter medication.                                   |
| atc_215a | character | ATC code of respondent's fifteenth over-the-counter medication.                                    |
| atc_131a | character | ATC code of respondent's first new prescription medication.                                        |
| atc_132a | character | ATC code of respondent's second new prescription medication.                                       |
| atc_133a | character | ATC code of respondent's third new prescription medication.                                        |
| atc_134a | character | ATC code of respondent's fourth new prescription medication.                                       |
| atc_135a | character | ATC code of respondent's fifth new prescription medication.                                        |
| atc_231a | character | ATC code of respondent's first new over-the-counter medication.                                    |
| atc_232a | character | ATC code of respondent's second new over-the-counter medication.                                   |
| atc_233a | character | ATC code of respondent's third new over-the-counter medication.                                    |
| atc_234a | character | ATC code of respondent's fourth new over-the-counter medication.                                   |
| atc_235a | character | ATC code of respondent's fifth new over-the-counter medication.                                    |
| mhr_101b | integer   | Response for when the first prescription medication was last taken (1 = Today, . . . , 6 = Never). |
| mhr_102b | integer   | Response for when the second prescription medication was last taken (1-6).                         |
| mhr_103b | integer   | Response for when the third prescription medication was last taken (1-6).                          |
| mhr_104b | integer   | Response for when the fourth prescription medication was last taken (1-6).                         |
| mhr_105b | integer   | Response for when the fifth prescription medication was last taken (1-6).                          |
| mhr_106b | integer   | Response for when the sixth prescription medication was last taken (1-6).                          |
| mhr_107b | integer   | Response for when the seventh prescription medication was last taken (1-6).                        |
| mhr_108b | integer   | Response for when the eighth prescription medication was last taken (1-6).                         |
| mhr_109b | integer   | Response for when the ninth prescription medication was last taken (1-6).                          |
| mhr_110b | integer   | Response for when the tenth prescription medication was last taken (1-6).                          |
| mhr_111b | integer   | Response for when the eleventh prescription medication was last taken (1-6).                       |

|          |                                                                                                            |
|----------|------------------------------------------------------------------------------------------------------------|
| mhr_112b | <a href="#">integer</a> Response for when the twelfth prescription medication was last taken (1-6).        |
| mhr_113b | <a href="#">integer</a> Response for when the thirteenth prescription medication was last taken (1-6).     |
| mhr_114b | <a href="#">integer</a> Response for when the fourteenth prescription medication was last taken (1-6).     |
| mhr_115b | <a href="#">integer</a> Response for when the fifteenth prescription medication was last taken (1-6).      |
| mhr_201b | <a href="#">integer</a> Response for when the first over-the-counter medication was last taken (1-6).      |
| mhr_202b | <a href="#">integer</a> Response for when the second over-the-counter medication was last taken (1-6).     |
| mhr_203b | <a href="#">integer</a> Response for when the third over-the-counter medication was last taken (1-6).      |
| mhr_204b | <a href="#">integer</a> Response for when the fourth over-the-counter medication was last taken (1-6).     |
| mhr_205b | <a href="#">integer</a> Response for when the fifth over-the-counter medication was last taken (1-6).      |
| mhr_206b | <a href="#">integer</a> Response for when the sixth over-the-counter medication was last taken (1-6).      |
| mhr_207b | <a href="#">integer</a> Response for when the seventh over-the-counter medication was last taken (1-6).    |
| mhr_208b | <a href="#">integer</a> Response for when the eighth over-the-counter medication was last taken (1-6).     |
| mhr_209b | <a href="#">integer</a> Response for when the ninth over-the-counter medication was last taken (1-6).      |
| mhr_210b | <a href="#">integer</a> Response for when the tenth over-the-counter medication was last taken (1-6).      |
| mhr_211b | <a href="#">integer</a> Response for when the eleventh over-the-counter medication was last taken (1-6).   |
| mhr_212b | <a href="#">integer</a> Response for when the twelfth over-the-counter medication was last taken (1-6).    |
| mhr_213b | <a href="#">integer</a> Response for when the thirteenth over-the-counter medication was last taken (1-6). |
| mhr_214b | <a href="#">integer</a> Response for when the fourteenth over-the-counter medication was last taken (1-6). |
| mhr_215b | <a href="#">integer</a> Response for when the fifteenth over-the-counter medication was last taken (1-6).  |
| mhr_131b | <a href="#">integer</a> Response for when the first new prescription medication was last taken (1-6).      |
| mhr_132b | <a href="#">integer</a> Response for when the second new prescription medication was last taken (1-6).     |

|          |                                                                                                   |
|----------|---------------------------------------------------------------------------------------------------|
| mhr_133b | <b>integer</b> Response for when the third new prescription medication was last taken (1-6).      |
| mhr_134b | <b>integer</b> Response for when the fourth new prescription medication was last taken (1-6).     |
| mhr_135b | <b>integer</b> Response for when the fifth new prescription medication was last taken (1-6).      |
| mhr_231b | <b>integer</b> Response for when the first new over-the-counter medication was last taken (1-6).  |
| mhr_232b | <b>integer</b> Response for when the second new over-the-counter medication was last taken (1-6). |
| mhr_233b | <b>integer</b> Response for when the third new over-the-counter medication was last taken (1-6).  |
| mhr_234b | <b>integer</b> Response for when the fourth new over-the-counter medication was last taken (1-6). |
| mhr_235b | <b>integer</b> Response for when the fifth new over-the-counter medication was last taken (1-6).  |

### Details

The function identifies calcium channel blockers based on ATC codes starting with "C08". It checks all medication variables provided in the input data frame.

```
Missing Data Codes:
- The function handles tagged NAs from the `is_calcium_channel_blocker` function and propagates them
```

### Value

**numeric** Returns 1 if the person is taking calcium channel blockers, 0 otherwise. If all medication information is missing, it returns a tagged NA.

### See Also

`is_calcium_channel_blocker`

### Examples

```
This is a wrapper function and is not intended to be called directly by the user.
See `is_calcium_channel_blocker` for usage examples.
```

---

|                 |                             |
|-----------------|-----------------------------|
| is_diabetes_med | <i>Diabetes medications</i> |
|-----------------|-----------------------------|

---

## Description

This function checks if a given medication is a diabetes drug. This function processes multiple inputs efficiently.

## Usage

```
is_diabetes_med(meucatc, npi_25b)
```

## Arguments

meucatc            **character** ATC code of the medication.  
npi\_25b            **integer** Time when the medication was last taken.

## Details

Identifies diabetes drugs based on ATC codes starting with "A10".

```
Missing Data Codes:
- `meucatc`: `9999996` (Not applicable), `9999997-9999999` (Missing)
- `npi_25b`: `6` (Not applicable), `7-9` (Missing)
```

## Value

**numeric** 1 if medication is a diabetes drug, 0 otherwise. If inputs are invalid or out of bounds, the function returns a tagged NA.

## Examples

```
Scalar usage: Single respondent
is_diabetes_med("A10BB09", 3)
Returns: 1

Example: Respondent has non-response values for all inputs.
result <- is_diabetes_med("9999998", 8)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

Multiple respondents
is_diabetes_med(c("A10BB09", "C09AA02"), c(3, 2))
Returns: c(1, 0)

Database usage: Applied to survey datasets
library(dplyr)
cycle3_meds |>
```

```
mutate(diabetes_med = is_diabetes_med(meucatc, np_i_25b)) |>
head()
```

---

```
is_diab_med_cycles1to2
```

*Diabetes medications - cycles 1-2*

---

### Description

This function checks if a person is taking diabetes drugs based on the provided Anatomical Therapeutic Chemical (ATC) codes for medications and the Canadian Health Measures Survey (CHMS) response for the time when the medication was last taken.

### Usage

```
is_diab_med_cycles1to2(
 atc_101a = NULL,
 atc_102a = NULL,
 atc_103a = NULL,
 atc_104a = NULL,
 atc_105a = NULL,
 atc_106a = NULL,
 atc_107a = NULL,
 atc_108a = NULL,
 atc_109a = NULL,
 atc_110a = NULL,
 atc_111a = NULL,
 atc_112a = NULL,
 atc_113a = NULL,
 atc_114a = NULL,
 atc_115a = NULL,
 atc_201a = NULL,
 atc_202a = NULL,
 atc_203a = NULL,
 atc_204a = NULL,
 atc_205a = NULL,
 atc_206a = NULL,
 atc_207a = NULL,
 atc_208a = NULL,
 atc_209a = NULL,
 atc_210a = NULL,
 atc_211a = NULL,
 atc_212a = NULL,
 atc_213a = NULL,
 atc_214a = NULL,
 atc_215a = NULL,
```

atc\_131a = NULL,  
atc\_132a = NULL,  
atc\_133a = NULL,  
atc\_134a = NULL,  
atc\_135a = NULL,  
atc\_231a = NULL,  
atc\_232a = NULL,  
atc\_233a = NULL,  
atc\_234a = NULL,  
atc\_235a = NULL,  
mhr\_101b = NULL,  
mhr\_102b = NULL,  
mhr\_103b = NULL,  
mhr\_104b = NULL,  
mhr\_105b = NULL,  
mhr\_106b = NULL,  
mhr\_107b = NULL,  
mhr\_108b = NULL,  
mhr\_109b = NULL,  
mhr\_110b = NULL,  
mhr\_111b = NULL,  
mhr\_112b = NULL,  
mhr\_113b = NULL,  
mhr\_114b = NULL,  
mhr\_115b = NULL,  
mhr\_201b = NULL,  
mhr\_202b = NULL,  
mhr\_203b = NULL,  
mhr\_204b = NULL,  
mhr\_205b = NULL,  
mhr\_206b = NULL,  
mhr\_207b = NULL,  
mhr\_208b = NULL,  
mhr\_209b = NULL,  
mhr\_210b = NULL,  
mhr\_211b = NULL,  
mhr\_212b = NULL,  
mhr\_213b = NULL,  
mhr\_214b = NULL,  
mhr\_215b = NULL,  
mhr\_131b = NULL,  
mhr\_132b = NULL,  
mhr\_133b = NULL,  
mhr\_134b = NULL,  
mhr\_135b = NULL,  
mhr\_231b = NULL,  
mhr\_232b = NULL,  
mhr\_233b = NULL,

```

 mhr_234b = NULL,
 mhr_235b = NULL
)

```

### Arguments

|          |           |                                                                  |
|----------|-----------|------------------------------------------------------------------|
| atc_101a | character | ATC code of respondent's first prescription medication.          |
| atc_102a | character | ATC code of respondent's second prescription medication.         |
| atc_103a | character | ATC code of respondent's third prescription medication.          |
| atc_104a | character | ATC code of respondent's fourth prescription medication.         |
| atc_105a | character | ATC code of respondent's fifth prescription medication.          |
| atc_106a | character | ATC code of respondent's sixth prescription medication.          |
| atc_107a | character | ATC code of respondent's seventh prescription medication.        |
| atc_108a | character | ATC code of respondent's eighth prescription medication.         |
| atc_109a | character | ATC code of respondent's ninth prescription medication.          |
| atc_110a | character | ATC code of respondent's tenth prescription medication.          |
| atc_111a | character | ATC code of respondent's eleventh prescription medication.       |
| atc_112a | character | ATC code of respondent's twelfth prescription medication.        |
| atc_113a | character | ATC code of respondent's thirteenth prescription medication.     |
| atc_114a | character | ATC code of respondent's fourteenth prescription medication.     |
| atc_115a | character | ATC code of respondent's fifteenth prescription medication.      |
| atc_201a | character | ATC code of respondent's first over-the-counter medication.      |
| atc_202a | character | ATC code of respondent's second over-the-counter medication.     |
| atc_203a | character | ATC code of respondent's third over-the-counter medication.      |
| atc_204a | character | ATC code of respondent's fourth over-the-counter medication.     |
| atc_205a | character | ATC code of respondent's fifth over-the-counter medication.      |
| atc_206a | character | ATC code of respondent's sixth over-the-counter medication.      |
| atc_207a | character | ATC code of respondent's seventh over-the-counter medication.    |
| atc_208a | character | ATC code of respondent's eighth over-the-counter medication.     |
| atc_209a | character | ATC code of respondent's ninth over-the-counter medication.      |
| atc_210a | character | ATC code of respondent's tenth over-the-counter medication.      |
| atc_211a | character | ATC code of respondent's eleventh over-the-counter medication.   |
| atc_212a | character | ATC code of respondent's twelfth over-the-counter medication.    |
| atc_213a | character | ATC code of respondent's thirteenth over-the-counter medication. |
| atc_214a | character | ATC code of respondent's fourteenth over-the-counter medication. |
| atc_215a | character | ATC code of respondent's fifteenth over-the-counter medication.  |
| atc_131a | character | ATC code of respondent's first new prescription medication.      |
| atc_132a | character | ATC code of respondent's second new prescription medication.     |
| atc_133a | character | ATC code of respondent's third new prescription medication.      |

|          |                                                                                                                |
|----------|----------------------------------------------------------------------------------------------------------------|
| atc_134a | <b>character</b> ATC code of respondent's fourth new prescription medication.                                  |
| atc_135a | <b>character</b> ATC code of respondent's fifth new prescription medication.                                   |
| atc_231a | <b>character</b> ATC code of respondent's first new over-the-counter medication.                               |
| atc_232a | <b>character</b> ATC code of respondent's second new over-the-counter medication.                              |
| atc_233a | <b>character</b> ATC code of respondent's third new over-the-counter medication.                               |
| atc_234a | <b>character</b> ATC code of respondent's fourth new over-the-counter medication.                              |
| atc_235a | <b>character</b> ATC code of respondent's fifth new over-the-counter medication.                               |
| mhr_101b | <b>integer</b> Response for when the first prescription medication was last taken (1 = Today, ..., 6 = Never). |
| mhr_102b | <b>integer</b> Response for when the second prescription medication was last taken (1-6).                      |
| mhr_103b | <b>integer</b> Response for when the third prescription medication was last taken (1-6).                       |
| mhr_104b | <b>integer</b> Response for when the fourth prescription medication was last taken (1-6).                      |
| mhr_105b | <b>integer</b> Response for when the fifth prescription medication was last taken (1-6).                       |
| mhr_106b | <b>integer</b> Response for when the sixth prescription medication was last taken (1-6).                       |
| mhr_107b | <b>integer</b> Response for when the seventh prescription medication was last taken (1-6).                     |
| mhr_108b | <b>integer</b> Response for when the eighth prescription medication was last taken (1-6).                      |
| mhr_109b | <b>integer</b> Response for when the ninth prescription medication was last taken (1-6).                       |
| mhr_110b | <b>integer</b> Response for when the tenth prescription medication was last taken (1-6).                       |
| mhr_111b | <b>integer</b> Response for when the eleventh prescription medication was last taken (1-6).                    |
| mhr_112b | <b>integer</b> Response for when the twelfth prescription medication was last taken (1-6).                     |
| mhr_113b | <b>integer</b> Response for when the thirteenth prescription medication was last taken (1-6).                  |
| mhr_114b | <b>integer</b> Response for when the fourteenth prescription medication was last taken (1-6).                  |
| mhr_115b | <b>integer</b> Response for when the fifteenth prescription medication was last taken (1-6).                   |
| mhr_201b | <b>integer</b> Response for when the first over-the-counter medication was last taken (1-6).                   |
| mhr_202b | <b>integer</b> Response for when the second over-the-counter medication was last taken (1-6).                  |
| mhr_203b | <b>integer</b> Response for when the third over-the-counter medication was last taken (1-6).                   |

|          |                                                                                                            |
|----------|------------------------------------------------------------------------------------------------------------|
| mhr_204b | <a href="#">integer</a> Response for when the fourth over-the-counter medication was last taken (1-6).     |
| mhr_205b | <a href="#">integer</a> Response for when the fifth over-the-counter medication was last taken (1-6).      |
| mhr_206b | <a href="#">integer</a> Response for when the sixth over-the-counter medication was last taken (1-6).      |
| mhr_207b | <a href="#">integer</a> Response for when the seventh over-the-counter medication was last taken (1-6).    |
| mhr_208b | <a href="#">integer</a> Response for when the eighth over-the-counter medication was last taken (1-6).     |
| mhr_209b | <a href="#">integer</a> Response for when the ninth over-the-counter medication was last taken (1-6).      |
| mhr_210b | <a href="#">integer</a> Response for when the tenth over-the-counter medication was last taken (1-6).      |
| mhr_211b | <a href="#">integer</a> Response for when the eleventh over-the-counter medication was last taken (1-6).   |
| mhr_212b | <a href="#">integer</a> Response for when the twelfth over-the-counter medication was last taken (1-6).    |
| mhr_213b | <a href="#">integer</a> Response for when the thirteenth over-the-counter medication was last taken (1-6). |
| mhr_214b | <a href="#">integer</a> Response for when the fourteenth over-the-counter medication was last taken (1-6). |
| mhr_215b | <a href="#">integer</a> Response for when the fifteenth over-the-counter medication was last taken (1-6).  |
| mhr_131b | <a href="#">integer</a> Response for when the first new prescription medication was last taken (1-6).      |
| mhr_132b | <a href="#">integer</a> Response for when the second new prescription medication was last taken (1-6).     |
| mhr_133b | <a href="#">integer</a> Response for when the third new prescription medication was last taken (1-6).      |
| mhr_134b | <a href="#">integer</a> Response for when the fourth new prescription medication was last taken (1-6).     |
| mhr_135b | <a href="#">integer</a> Response for when the fifth new prescription medication was last taken (1-6).      |
| mhr_231b | <a href="#">integer</a> Response for when the first new over-the-counter medication was last taken (1-6).  |
| mhr_232b | <a href="#">integer</a> Response for when the second new over-the-counter medication was last taken (1-6). |
| mhr_233b | <a href="#">integer</a> Response for when the third new over-the-counter medication was last taken (1-6).  |
| mhr_234b | <a href="#">integer</a> Response for when the fourth new over-the-counter medication was last taken (1-6). |
| mhr_235b | <a href="#">integer</a> Response for when the fifth new over-the-counter medication was last taken (1-6).  |

**Details**

The function identifies diabetes drugs based on ATC codes starting with "A10". It checks all medication variables provided in the input data frame.

```
Missing Data Codes:
- The function handles tagged NAs from the `is_diabetes_med` function and propagates them.
```

**Value**

**numeric** Returns 1 if the person is taking any diabetes drugs, 0 otherwise. If all medication information is missing, it returns a tagged NA.

**See Also**

is\_diabetes\_med

**Examples**

```
This is a wrapper function and is not intended to be called directly by the user.
See `is_diabetes_med` for usage examples.
```

---

|             |                  |
|-------------|------------------|
| is_diuretic | <i>Diuretics</i> |
|-------------|------------------|

---

**Description**

This function checks if a given medication is a diuretic. This function processes multiple inputs efficiently.

**Usage**

```
is_diuretic(meucatc, npi_25b)
```

**Arguments**

meucatc            **character** ATC code of the medication.  
npi\_25b            **integer** Time when the medication was last taken.

**Details**

Identifies diuretics based on ATC codes starting with "C03", excluding specific sub-codes.

```
Missing Data Codes:
- `meucatc`: `9999996` (Not applicable), `9999997-9999999` (Missing)
- `npi_25b`: `6` (Not applicable), `7-9` (Missing)
```

**Value**

**numeric** 1 if medication is a diuretic, 0 otherwise. If inputs are invalid or out of bounds, the function returns a tagged NA.

**Examples**

```
Scalar usage: Single respondent
is_diuretic("C03AA03", 3)
Returns: 1

Example: Respondent has non-response values for all inputs.
result <- is_diuretic("9999998", 8)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

Multiple respondents
is_diuretic(c("C03AA03", "C03BA08"), c(3, 2))
Returns: c(1, 0)

Database usage: Applied to survey datasets
library(dplyr)
cycle3_meds |>
 mutate(diuretic = is_diuretic(meucatc, npi_25b)) |>
 head()
```

---

is\_diur\_med\_cycles1to2

*Diuretics - cycles 1-2*

---

**Description**

This function checks if a person is taking diuretics based on the provided Anatomical Therapeutic Chemical (ATC) codes for medications and the Canadian Health Measures Survey (CHMS) response for the time when the medication was last taken.

**Usage**

```
is_diur_med_cycles1to2(
 atc_101a = NULL,
 atc_102a = NULL,
 atc_103a = NULL,
 atc_104a = NULL,
 atc_105a = NULL,
 atc_106a = NULL,
 atc_107a = NULL,
 atc_108a = NULL,
```

atc\_109a = NULL,  
atc\_110a = NULL,  
atc\_111a = NULL,  
atc\_112a = NULL,  
atc\_113a = NULL,  
atc\_114a = NULL,  
atc\_115a = NULL,  
atc\_201a = NULL,  
atc\_202a = NULL,  
atc\_203a = NULL,  
atc\_204a = NULL,  
atc\_205a = NULL,  
atc\_206a = NULL,  
atc\_207a = NULL,  
atc\_208a = NULL,  
atc\_209a = NULL,  
atc\_210a = NULL,  
atc\_211a = NULL,  
atc\_212a = NULL,  
atc\_213a = NULL,  
atc\_214a = NULL,  
atc\_215a = NULL,  
atc\_131a = NULL,  
atc\_132a = NULL,  
atc\_133a = NULL,  
atc\_134a = NULL,  
atc\_135a = NULL,  
atc\_231a = NULL,  
atc\_232a = NULL,  
atc\_233a = NULL,  
atc\_234a = NULL,  
atc\_235a = NULL,  
mhr\_101b = NULL,  
mhr\_102b = NULL,  
mhr\_103b = NULL,  
mhr\_104b = NULL,  
mhr\_105b = NULL,  
mhr\_106b = NULL,  
mhr\_107b = NULL,  
mhr\_108b = NULL,  
mhr\_109b = NULL,  
mhr\_110b = NULL,  
mhr\_111b = NULL,  
mhr\_112b = NULL,  
mhr\_113b = NULL,  
mhr\_114b = NULL,  
mhr\_115b = NULL,  
mhr\_201b = NULL,

```

mhr_202b = NULL,
mhr_203b = NULL,
mhr_204b = NULL,
mhr_205b = NULL,
mhr_206b = NULL,
mhr_207b = NULL,
mhr_208b = NULL,
mhr_209b = NULL,
mhr_210b = NULL,
mhr_211b = NULL,
mhr_212b = NULL,
mhr_213b = NULL,
mhr_214b = NULL,
mhr_215b = NULL,
mhr_131b = NULL,
mhr_132b = NULL,
mhr_133b = NULL,
mhr_134b = NULL,
mhr_135b = NULL,
mhr_231b = NULL,
mhr_232b = NULL,
mhr_233b = NULL,
mhr_234b = NULL,
mhr_235b = NULL
)

```

### Arguments

|          |                                                                               |
|----------|-------------------------------------------------------------------------------|
| atc_101a | <b>character</b> ATC code of respondent's first prescription medication.      |
| atc_102a | <b>character</b> ATC code of respondent's second prescription medication.     |
| atc_103a | <b>character</b> ATC code of respondent's third prescription medication.      |
| atc_104a | <b>character</b> ATC code of respondent's fourth prescription medication.     |
| atc_105a | <b>character</b> ATC code of respondent's fifth prescription medication.      |
| atc_106a | <b>character</b> ATC code of respondent's sixth prescription medication.      |
| atc_107a | <b>character</b> ATC code of respondent's seventh prescription medication.    |
| atc_108a | <b>character</b> ATC code of respondent's eighth prescription medication.     |
| atc_109a | <b>character</b> ATC code of respondent's ninth prescription medication.      |
| atc_110a | <b>character</b> ATC code of respondent's tenth prescription medication.      |
| atc_111a | <b>character</b> ATC code of respondent's eleventh prescription medication.   |
| atc_112a | <b>character</b> ATC code of respondent's twelfth prescription medication.    |
| atc_113a | <b>character</b> ATC code of respondent's thirteenth prescription medication. |
| atc_114a | <b>character</b> ATC code of respondent's fourteenth prescription medication. |
| atc_115a | <b>character</b> ATC code of respondent's fifteenth prescription medication.  |
| atc_201a | <b>character</b> ATC code of respondent's first over-the-counter medication.  |

|          |           |                                                                                                 |
|----------|-----------|-------------------------------------------------------------------------------------------------|
| atc_202a | character | ATC code of respondent's second over-the-counter medication.                                    |
| atc_203a | character | ATC code of respondent's third over-the-counter medication.                                     |
| atc_204a | character | ATC code of respondent's fourth over-the-counter medication.                                    |
| atc_205a | character | ATC code of respondent's fifth over-the-counter medication.                                     |
| atc_206a | character | ATC code of respondent's sixth over-the-counter medication.                                     |
| atc_207a | character | ATC code of respondent's seventh over-the-counter medication.                                   |
| atc_208a | character | ATC code of respondent's eighth over-the-counter medication.                                    |
| atc_209a | character | ATC code of respondent's ninth over-the-counter medication.                                     |
| atc_210a | character | ATC code of respondent's tenth over-the-counter medication.                                     |
| atc_211a | character | ATC code of respondent's eleventh over-the-counter medication.                                  |
| atc_212a | character | ATC code of respondent's twelfth over-the-counter medication.                                   |
| atc_213a | character | ATC code of respondent's thirteenth over-the-counter medication.                                |
| atc_214a | character | ATC code of respondent's fourteenth over-the-counter medication.                                |
| atc_215a | character | ATC code of respondent's fifteenth over-the-counter medication.                                 |
| atc_131a | character | ATC code of respondent's first new prescription medication.                                     |
| atc_132a | character | ATC code of respondent's second new prescription medication.                                    |
| atc_133a | character | ATC code of respondent's third new prescription medication.                                     |
| atc_134a | character | ATC code of respondent's fourth new prescription medication.                                    |
| atc_135a | character | ATC code of respondent's fifth new prescription medication.                                     |
| atc_231a | character | ATC code of respondent's first new over-the-counter medication.                                 |
| atc_232a | character | ATC code of respondent's second new over-the-counter medication.                                |
| atc_233a | character | ATC code of respondent's third new over-the-counter medication.                                 |
| atc_234a | character | ATC code of respondent's fourth new over-the-counter medication.                                |
| atc_235a | character | ATC code of respondent's fifth new over-the-counter medication.                                 |
| mhr_101b | integer   | Response for when the first prescription medication was last taken (1 = Today, ..., 6 = Never). |
| mhr_102b | integer   | Response for when the second prescription medication was last taken (1-6).                      |
| mhr_103b | integer   | Response for when the third prescription medication was last taken (1-6).                       |
| mhr_104b | integer   | Response for when the fourth prescription medication was last taken (1-6).                      |
| mhr_105b | integer   | Response for when the fifth prescription medication was last taken (1-6).                       |
| mhr_106b | integer   | Response for when the sixth prescription medication was last taken (1-6).                       |
| mhr_107b | integer   | Response for when the seventh prescription medication was last taken (1-6).                     |
| mhr_108b | integer   | Response for when the eighth prescription medication was last taken (1-6).                      |

|          |                                                                                                            |
|----------|------------------------------------------------------------------------------------------------------------|
| mhr_109b | <a href="#">integer</a> Response for when the ninth prescription medication was last taken (1-6).          |
| mhr_110b | <a href="#">integer</a> Response for when the tenth prescription medication was last taken (1-6).          |
| mhr_111b | <a href="#">integer</a> Response for when the eleventh prescription medication was last taken (1-6).       |
| mhr_112b | <a href="#">integer</a> Response for when the twelfth prescription medication was last taken (1-6).        |
| mhr_113b | <a href="#">integer</a> Response for when the thirteenth prescription medication was last taken (1-6).     |
| mhr_114b | <a href="#">integer</a> Response for when the fourteenth prescription medication was last taken (1-6).     |
| mhr_115b | <a href="#">integer</a> Response for when the fifteenth prescription medication was last taken (1-6).      |
| mhr_201b | <a href="#">integer</a> Response for when the first over-the-counter medication was last taken (1-6).      |
| mhr_202b | <a href="#">integer</a> Response for when the second over-the-counter medication was last taken (1-6).     |
| mhr_203b | <a href="#">integer</a> Response for when the third over-the-counter medication was last taken (1-6).      |
| mhr_204b | <a href="#">integer</a> Response for when the fourth over-the-counter medication was last taken (1-6).     |
| mhr_205b | <a href="#">integer</a> Response for when the fifth over-the-counter medication was last taken (1-6).      |
| mhr_206b | <a href="#">integer</a> Response for when the sixth over-the-counter medication was last taken (1-6).      |
| mhr_207b | <a href="#">integer</a> Response for when the seventh over-the-counter medication was last taken (1-6).    |
| mhr_208b | <a href="#">integer</a> Response for when the eighth over-the-counter medication was last taken (1-6).     |
| mhr_209b | <a href="#">integer</a> Response for when the ninth over-the-counter medication was last taken (1-6).      |
| mhr_210b | <a href="#">integer</a> Response for when the tenth over-the-counter medication was last taken (1-6).      |
| mhr_211b | <a href="#">integer</a> Response for when the eleventh over-the-counter medication was last taken (1-6).   |
| mhr_212b | <a href="#">integer</a> Response for when the twelfth over-the-counter medication was last taken (1-6).    |
| mhr_213b | <a href="#">integer</a> Response for when the thirteenth over-the-counter medication was last taken (1-6). |
| mhr_214b | <a href="#">integer</a> Response for when the fourteenth over-the-counter medication was last taken (1-6). |

|          |                                                                                                   |
|----------|---------------------------------------------------------------------------------------------------|
| mhr_215b | <b>integer</b> Response for when the fifteenth over-the-counter medication was last taken (1-6).  |
| mhr_131b | <b>integer</b> Response for when the first new prescription medication was last taken (1-6).      |
| mhr_132b | <b>integer</b> Response for when the second new prescription medication was last taken (1-6).     |
| mhr_133b | <b>integer</b> Response for when the third new prescription medication was last taken (1-6).      |
| mhr_134b | <b>integer</b> Response for when the fourth new prescription medication was last taken (1-6).     |
| mhr_135b | <b>integer</b> Response for when the fifth new prescription medication was last taken (1-6).      |
| mhr_231b | <b>integer</b> Response for when the first new over-the-counter medication was last taken (1-6).  |
| mhr_232b | <b>integer</b> Response for when the second new over-the-counter medication was last taken (1-6). |
| mhr_233b | <b>integer</b> Response for when the third new over-the-counter medication was last taken (1-6).  |
| mhr_234b | <b>integer</b> Response for when the fourth new over-the-counter medication was last taken (1-6). |
| mhr_235b | <b>integer</b> Response for when the fifth new over-the-counter medication was last taken (1-6).  |

### Details

The function identifies diuretics based on ATC codes starting with "C03", excluding specific sub-codes. It checks all medication variables provided in the input data frame.

**\*\*Missing Data Codes:\*\***  
 - The function handles tagged NAs from the ``is_diuretic`` function and propagates them.

### Value

**numeric** Returns 1 if the person is taking diuretics, 0 otherwise. If all medication information is missing, it returns a tagged NA.

### See Also

`is_diuretic`

### Examples

```
This is a wrapper function and is not intended to be called directly by the user.
See `is_diuretic` for usage examples.
```

---

```
is_lowest_income_quintile
 Lowest income quintile indicator
```

---

### Description

This function checks if an individual's income category corresponds to the lowest income quintile.

### Usage

```
is_lowest_income_quintile(income_quintile)
```

### Arguments

```
income_quintile
```

[integer](#) A categorical vector indicating the income category as defined by the `categorize_income_quintile` function.

### Details

This function identifies individuals in the lowest income quintile, a common indicator for socioeconomic disadvantage.

```
Missing Data Codes:
```

```
- Propagates tagged NAs from the input `income_quintile`.
```

### Value

[integer](#) Whether the individual is in the lowest income quintile:

- 1: In the lowest income quintile
- 2: Not in the lowest income quintile
- `haven::tagged_na("a")`: Not applicable
- `haven::tagged_na("b")`: Missing

### See Also

[categorize\\_income\\_quintile\(\)](#)

### Examples

```
Scalar usage: Single respondent
Example 1: Check if an income category of 3 is in the lowest quintile
is_lowest_income_quintile(3)
Output: 2

Example 2: Check if an income category of 1 is in the lowest quintile
is_lowest_income_quintile(1)
```

```

Output: 1

Multiple respondents
is_lowest_income_quintile(c(3, 1, 5))
Returns: c(2, 1, 2)

Database usage: Applied to survey datasets
library(dplyr)
cycle4 |>
 mutate(adj_hh_income = calculate_household_income(thi_01, dhhhsz)) |>
 mutate(income_category = categorize_income_quintile(adj_hh_income)) |>
 mutate(in_lowest_quintile = is_lowest_income_quintile(income_category)) |>
 head()

```

---

is\_misc\_htn\_med\_cycles1to2

*Other anti-hypertensive medications - cycles 1-2*

---

### Description

This function checks if a person is taking another type of anti-hypertensive medication based on the provided Anatomical Therapeutic Chemical (ATC) codes for medications and the Canadian Health Measures Survey (CHMS) response for the time when the medication was last taken.

### Usage

```

is_misc_htn_med_cycles1to2(
 atc_101a = NULL,
 atc_102a = NULL,
 atc_103a = NULL,
 atc_104a = NULL,
 atc_105a = NULL,
 atc_106a = NULL,
 atc_107a = NULL,
 atc_108a = NULL,
 atc_109a = NULL,
 atc_110a = NULL,
 atc_111a = NULL,
 atc_112a = NULL,
 atc_113a = NULL,
 atc_114a = NULL,
 atc_115a = NULL,
 atc_201a = NULL,
 atc_202a = NULL,
 atc_203a = NULL,
 atc_204a = NULL,
 atc_205a = NULL,

```

atc\_206a = NULL,  
atc\_207a = NULL,  
atc\_208a = NULL,  
atc\_209a = NULL,  
atc\_210a = NULL,  
atc\_211a = NULL,  
atc\_212a = NULL,  
atc\_213a = NULL,  
atc\_214a = NULL,  
atc\_215a = NULL,  
atc\_131a = NULL,  
atc\_132a = NULL,  
atc\_133a = NULL,  
atc\_134a = NULL,  
atc\_135a = NULL,  
atc\_231a = NULL,  
atc\_232a = NULL,  
atc\_233a = NULL,  
atc\_234a = NULL,  
atc\_235a = NULL,  
mhr\_101b = NULL,  
mhr\_102b = NULL,  
mhr\_103b = NULL,  
mhr\_104b = NULL,  
mhr\_105b = NULL,  
mhr\_106b = NULL,  
mhr\_107b = NULL,  
mhr\_108b = NULL,  
mhr\_109b = NULL,  
mhr\_110b = NULL,  
mhr\_111b = NULL,  
mhr\_112b = NULL,  
mhr\_113b = NULL,  
mhr\_114b = NULL,  
mhr\_115b = NULL,  
mhr\_201b = NULL,  
mhr\_202b = NULL,  
mhr\_203b = NULL,  
mhr\_204b = NULL,  
mhr\_205b = NULL,  
mhr\_206b = NULL,  
mhr\_207b = NULL,  
mhr\_208b = NULL,  
mhr\_209b = NULL,  
mhr\_210b = NULL,  
mhr\_211b = NULL,  
mhr\_212b = NULL,  
mhr\_213b = NULL,

```
mhr_214b = NULL,
mhr_215b = NULL,
mhr_131b = NULL,
mhr_132b = NULL,
mhr_133b = NULL,
mhr_134b = NULL,
mhr_135b = NULL,
mhr_231b = NULL,
mhr_232b = NULL,
mhr_233b = NULL,
mhr_234b = NULL,
mhr_235b = NULL
)
```

**Arguments**

|          |                                                                                         |
|----------|-----------------------------------------------------------------------------------------|
| atc_101a | <a href="#">character</a> ATC code of respondent's first prescription medication.       |
| atc_102a | <a href="#">character</a> ATC code of respondent's second prescription medication.      |
| atc_103a | <a href="#">character</a> ATC code of respondent's third prescription medication.       |
| atc_104a | <a href="#">character</a> ATC code of respondent's fourth prescription medication.      |
| atc_105a | <a href="#">character</a> ATC code of respondent's fifth prescription medication.       |
| atc_106a | <a href="#">character</a> ATC code of respondent's sixth prescription medication.       |
| atc_107a | <a href="#">character</a> ATC code of respondent's seventh prescription medication.     |
| atc_108a | <a href="#">character</a> ATC code of respondent's eighth prescription medication.      |
| atc_109a | <a href="#">character</a> ATC code of respondent's ninth prescription medication.       |
| atc_110a | <a href="#">character</a> ATC code of respondent's tenth prescription medication.       |
| atc_111a | <a href="#">character</a> ATC code of respondent's eleventh prescription medication.    |
| atc_112a | <a href="#">character</a> ATC code of respondent's twelfth prescription medication.     |
| atc_113a | <a href="#">character</a> ATC code of respondent's thirteenth prescription medication.  |
| atc_114a | <a href="#">character</a> ATC code of respondent's fourteenth prescription medication.  |
| atc_115a | <a href="#">character</a> ATC code of respondent's fifteenth prescription medication.   |
| atc_201a | <a href="#">character</a> ATC code of respondent's first over-the-counter medication.   |
| atc_202a | <a href="#">character</a> ATC code of respondent's second over-the-counter medication.  |
| atc_203a | <a href="#">character</a> ATC code of respondent's third over-the-counter medication.   |
| atc_204a | <a href="#">character</a> ATC code of respondent's fourth over-the-counter medication.  |
| atc_205a | <a href="#">character</a> ATC code of respondent's fifth over-the-counter medication.   |
| atc_206a | <a href="#">character</a> ATC code of respondent's sixth over-the-counter medication.   |
| atc_207a | <a href="#">character</a> ATC code of respondent's seventh over-the-counter medication. |
| atc_208a | <a href="#">character</a> ATC code of respondent's eighth over-the-counter medication.  |
| atc_209a | <a href="#">character</a> ATC code of respondent's ninth over-the-counter medication.   |
| atc_210a | <a href="#">character</a> ATC code of respondent's tenth over-the-counter medication.   |

|          |                                                                                                                   |
|----------|-------------------------------------------------------------------------------------------------------------------|
| atc_211a | <b>character</b> ATC code of respondent's eleventh over-the-counter medication.                                   |
| atc_212a | <b>character</b> ATC code of respondent's twelfth over-the-counter medication.                                    |
| atc_213a | <b>character</b> ATC code of respondent's thirteenth over-the-counter medication.                                 |
| atc_214a | <b>character</b> ATC code of respondent's fourteenth over-the-counter medication.                                 |
| atc_215a | <b>character</b> ATC code of respondent's fifteenth over-the-counter medication.                                  |
| atc_131a | <b>character</b> ATC code of respondent's first new prescription medication.                                      |
| atc_132a | <b>character</b> ATC code of respondent's second new prescription medication.                                     |
| atc_133a | <b>character</b> ATC code of respondent's third new prescription medication.                                      |
| atc_134a | <b>character</b> ATC code of respondent's fourth new prescription medication.                                     |
| atc_135a | <b>character</b> ATC code of respondent's fifth new prescription medication.                                      |
| atc_231a | <b>character</b> ATC code of respondent's first new over-the-counter medication.                                  |
| atc_232a | <b>character</b> ATC code of respondent's second new over-the-counter medication.                                 |
| atc_233a | <b>character</b> ATC code of respondent's third new over-the-counter medication.                                  |
| atc_234a | <b>character</b> ATC code of respondent's fourth new over-the-counter medication.                                 |
| atc_235a | <b>character</b> ATC code of respondent's fifth new over-the-counter medication.                                  |
| mhr_101b | <b>integer</b> Response for when the first prescription medication was last taken (1 = Today, . . . , 6 = Never). |
| mhr_102b | <b>integer</b> Response for when the second prescription medication was last taken (1-6).                         |
| mhr_103b | <b>integer</b> Response for when the third prescription medication was last taken (1-6).                          |
| mhr_104b | <b>integer</b> Response for when the fourth prescription medication was last taken (1-6).                         |
| mhr_105b | <b>integer</b> Response for when the fifth prescription medication was last taken (1-6).                          |
| mhr_106b | <b>integer</b> Response for when the sixth prescription medication was last taken (1-6).                          |
| mhr_107b | <b>integer</b> Response for when the seventh prescription medication was last taken (1-6).                        |
| mhr_108b | <b>integer</b> Response for when the eighth prescription medication was last taken (1-6).                         |
| mhr_109b | <b>integer</b> Response for when the ninth prescription medication was last taken (1-6).                          |
| mhr_110b | <b>integer</b> Response for when the tenth prescription medication was last taken (1-6).                          |
| mhr_111b | <b>integer</b> Response for when the eleventh prescription medication was last taken (1-6).                       |
| mhr_112b | <b>integer</b> Response for when the twelfth prescription medication was last taken (1-6).                        |
| mhr_113b | <b>integer</b> Response for when the thirteenth prescription medication was last taken (1-6).                     |

|          |                                                                                                   |
|----------|---------------------------------------------------------------------------------------------------|
| mhr_114b | <b>integer</b> Response for when the fourteenth prescription medication was last taken (1-6).     |
| mhr_115b | <b>integer</b> Response for when the fifteenth prescription medication was last taken (1-6).      |
| mhr_201b | <b>integer</b> Response for when the first over-the-counter medication was last taken (1-6).      |
| mhr_202b | <b>integer</b> Response for when the second over-the-counter medication was last taken (1-6).     |
| mhr_203b | <b>integer</b> Response for when the third over-the-counter medication was last taken (1-6).      |
| mhr_204b | <b>integer</b> Response for when the fourth over-the-counter medication was last taken (1-6).     |
| mhr_205b | <b>integer</b> Response for when the fifth over-the-counter medication was last taken (1-6).      |
| mhr_206b | <b>integer</b> Response for when the sixth over-the-counter medication was last taken (1-6).      |
| mhr_207b | <b>integer</b> Response for when the seventh over-the-counter medication was last taken (1-6).    |
| mhr_208b | <b>integer</b> Response for when the eighth over-the-counter medication was last taken (1-6).     |
| mhr_209b | <b>integer</b> Response for when the ninth over-the-counter medication was last taken (1-6).      |
| mhr_210b | <b>integer</b> Response for when the tenth over-the-counter medication was last taken (1-6).      |
| mhr_211b | <b>integer</b> Response for when the eleventh over-the-counter medication was last taken (1-6).   |
| mhr_212b | <b>integer</b> Response for when the twelfth over-the-counter medication was last taken (1-6).    |
| mhr_213b | <b>integer</b> Response for when the thirteenth over-the-counter medication was last taken (1-6). |
| mhr_214b | <b>integer</b> Response for when the fourteenth over-the-counter medication was last taken (1-6). |
| mhr_215b | <b>integer</b> Response for when the fifteenth over-the-counter medication was last taken (1-6).  |
| mhr_131b | <b>integer</b> Response for when the first new prescription medication was last taken (1-6).      |
| mhr_132b | <b>integer</b> Response for when the second new prescription medication was last taken (1-6).     |
| mhr_133b | <b>integer</b> Response for when the third new prescription medication was last taken (1-6).      |
| mhr_134b | <b>integer</b> Response for when the fourth new prescription medication was last taken (1-6).     |

|          |                                                                                                   |
|----------|---------------------------------------------------------------------------------------------------|
| mhr_135b | <b>integer</b> Response for when the fifth new prescription medication was last taken (1-6).      |
| mhr_231b | <b>integer</b> Response for when the first new over-the-counter medication was last taken (1-6).  |
| mhr_232b | <b>integer</b> Response for when the second new over-the-counter medication was last taken (1-6). |
| mhr_233b | <b>integer</b> Response for when the third new over-the-counter medication was last taken (1-6).  |
| mhr_234b | <b>integer</b> Response for when the fourth new over-the-counter medication was last taken (1-6). |
| mhr_235b | <b>integer</b> Response for when the fifth new over-the-counter medication was last taken (1-6).  |

### Details

The function identifies other anti-hypertensive drugs based on ATC codes starting with "C02", excluding a specific sub-code. It checks all medication variables provided in the input data frame.

**\*\*Missing Data Codes:\*\***

- The function handles tagged NAs from the ``is_other_antihtn_med`` function and propagates them.

### Value

**numeric** Returns 1 if the person is taking another type of anti-hypertensive medication, 0 otherwise. If all medication information is missing, it returns a tagged NA.

### See Also

`is_other_antihtn_med`

### Examples

```
This is a wrapper function and is not intended to be called directly by the user.
See `is_other_antihtn_med` for usage examples.
```

---

is\_nsaid

*Non-steroidal anti-inflammatory drugs (NSAIDs)*

---

### Description

This function checks if a given medication is an NSAID. This function processes multiple inputs efficiently.

### Usage

```
is_nsaid(meucatc, npi_25b)
```

**Arguments**

meucatc            **character** ATC code of the medication.  
 npi\_25b            **integer** Time when the medication was last taken.

**Details**

Identifies NSAIDs based on ATC codes starting with "M01A".

```

Missing Data Codes:
- `meucatc`: `9999996` (Not applicable), `9999997-9999999` (Missing)
- `npi_25b`: `6` (Not applicable), `7-9` (Missing)

```

**Value**

**numeric** 1 if medication is an NSAID, 0 otherwise. If inputs are invalid or out of bounds, the function returns a tagged NA.

**Examples**

```

Scalar usage: Single respondent
is_nsaid("M01AB05", 1)
Returns: 1

Example: Respondent has non-response values for all inputs.
result <- is_nsaid("9999998", 8)
result # Shows: NA
haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

Multiple respondents
is_nsaid(c("M01AB05", "A10BB09"), c(1, 3))
Returns: c(1, 0)

Database usage: Applied to survey datasets
library(dplyr)
cycle3_meds |>
 mutate(nsaid = is_nsaid(meucatc, npi_25b)) |>
 head()

```

---

is\_nsaid\_med\_cycles1to2

*Non-steroidal anti-inflammatory drugs (NSAIDs) - cycles 1-2*

---

**Description**

This function checks if a person is taking any NSAIDs based on the provided Anatomical Therapeutic Chemical (ATC) codes for medications and the Canadian Health Measures Survey (CHMS) response for the time when the medication was last taken.

**Usage**

```
is_nsaid_med_cycles1to2(
 atc_101a = NULL,
 atc_102a = NULL,
 atc_103a = NULL,
 atc_104a = NULL,
 atc_105a = NULL,
 atc_106a = NULL,
 atc_107a = NULL,
 atc_108a = NULL,
 atc_109a = NULL,
 atc_110a = NULL,
 atc_111a = NULL,
 atc_112a = NULL,
 atc_113a = NULL,
 atc_114a = NULL,
 atc_115a = NULL,
 atc_201a = NULL,
 atc_202a = NULL,
 atc_203a = NULL,
 atc_204a = NULL,
 atc_205a = NULL,
 atc_206a = NULL,
 atc_207a = NULL,
 atc_208a = NULL,
 atc_209a = NULL,
 atc_210a = NULL,
 atc_211a = NULL,
 atc_212a = NULL,
 atc_213a = NULL,
 atc_214a = NULL,
 atc_215a = NULL,
 atc_131a = NULL,
 atc_132a = NULL,
 atc_133a = NULL,
 atc_134a = NULL,
 atc_135a = NULL,
 atc_231a = NULL,
 atc_232a = NULL,
 atc_233a = NULL,
 atc_234a = NULL,
 atc_235a = NULL,
 mhr_101b = NULL,
 mhr_102b = NULL,
 mhr_103b = NULL,
 mhr_104b = NULL,
 mhr_105b = NULL,
 mhr_106b = NULL,
)
```

```
mhr_107b = NULL,
mhr_108b = NULL,
mhr_109b = NULL,
mhr_110b = NULL,
mhr_111b = NULL,
mhr_112b = NULL,
mhr_113b = NULL,
mhr_114b = NULL,
mhr_115b = NULL,
mhr_201b = NULL,
mhr_202b = NULL,
mhr_203b = NULL,
mhr_204b = NULL,
mhr_205b = NULL,
mhr_206b = NULL,
mhr_207b = NULL,
mhr_208b = NULL,
mhr_209b = NULL,
mhr_210b = NULL,
mhr_211b = NULL,
mhr_212b = NULL,
mhr_213b = NULL,
mhr_214b = NULL,
mhr_215b = NULL,
mhr_131b = NULL,
mhr_132b = NULL,
mhr_133b = NULL,
mhr_134b = NULL,
mhr_135b = NULL,
mhr_231b = NULL,
mhr_232b = NULL,
mhr_233b = NULL,
mhr_234b = NULL,
mhr_235b = NULL
)
```

### Arguments

|          |                                                                                     |
|----------|-------------------------------------------------------------------------------------|
| atc_101a | <a href="#">character</a> ATC code of respondent's first prescription medication.   |
| atc_102a | <a href="#">character</a> ATC code of respondent's second prescription medication.  |
| atc_103a | <a href="#">character</a> ATC code of respondent's third prescription medication.   |
| atc_104a | <a href="#">character</a> ATC code of respondent's fourth prescription medication.  |
| atc_105a | <a href="#">character</a> ATC code of respondent's fifth prescription medication.   |
| atc_106a | <a href="#">character</a> ATC code of respondent's sixth prescription medication.   |
| atc_107a | <a href="#">character</a> ATC code of respondent's seventh prescription medication. |
| atc_108a | <a href="#">character</a> ATC code of respondent's eighth prescription medication.  |

|          |           |                                                                                                 |
|----------|-----------|-------------------------------------------------------------------------------------------------|
| atc_109a | character | ATC code of respondent's ninth prescription medication.                                         |
| atc_110a | character | ATC code of respondent's tenth prescription medication.                                         |
| atc_111a | character | ATC code of respondent's eleventh prescription medication.                                      |
| atc_112a | character | ATC code of respondent's twelfth prescription medication.                                       |
| atc_113a | character | ATC code of respondent's thirteenth prescription medication.                                    |
| atc_114a | character | ATC code of respondent's fourteenth prescription medication.                                    |
| atc_115a | character | ATC code of respondent's fifteenth prescription medication.                                     |
| atc_201a | character | ATC code of respondent's first over-the-counter medication.                                     |
| atc_202a | character | ATC code of respondent's second over-the-counter medication.                                    |
| atc_203a | character | ATC code of respondent's third over-the-counter medication.                                     |
| atc_204a | character | ATC code of respondent's fourth over-the-counter medication.                                    |
| atc_205a | character | ATC code of respondent's fifth over-the-counter medication.                                     |
| atc_206a | character | ATC code of respondent's sixth over-the-counter medication.                                     |
| atc_207a | character | ATC code of respondent's seventh over-the-counter medication.                                   |
| atc_208a | character | ATC code of respondent's eighth over-the-counter medication.                                    |
| atc_209a | character | ATC code of respondent's ninth over-the-counter medication.                                     |
| atc_210a | character | ATC code of respondent's tenth over-the-counter medication.                                     |
| atc_211a | character | ATC code of respondent's eleventh over-the-counter medication.                                  |
| atc_212a | character | ATC code of respondent's twelfth over-the-counter medication.                                   |
| atc_213a | character | ATC code of respondent's thirteenth over-the-counter medication.                                |
| atc_214a | character | ATC code of respondent's fourteenth over-the-counter medication.                                |
| atc_215a | character | ATC code of respondent's fifteenth over-the-counter medication.                                 |
| atc_131a | character | ATC code of respondent's first new prescription medication.                                     |
| atc_132a | character | ATC code of respondent's second new prescription medication.                                    |
| atc_133a | character | ATC code of respondent's third new prescription medication.                                     |
| atc_134a | character | ATC code of respondent's fourth new prescription medication.                                    |
| atc_135a | character | ATC code of respondent's fifth new prescription medication.                                     |
| atc_231a | character | ATC code of respondent's first new over-the-counter medication.                                 |
| atc_232a | character | ATC code of respondent's second new over-the-counter medication.                                |
| atc_233a | character | ATC code of respondent's third new over-the-counter medication.                                 |
| atc_234a | character | ATC code of respondent's fourth new over-the-counter medication.                                |
| atc_235a | character | ATC code of respondent's fifth new over-the-counter medication.                                 |
| mhr_101b | integer   | Response for when the first prescription medication was last taken (1 = Today, ..., 6 = Never). |
| mhr_102b | integer   | Response for when the second prescription medication was last taken (1-6).                      |
| mhr_103b | integer   | Response for when the third prescription medication was last taken (1-6).                       |

|          |                                                                                                         |
|----------|---------------------------------------------------------------------------------------------------------|
| mhr_104b | <a href="#">integer</a> Response for when the fourth prescription medication was last taken (1-6).      |
| mhr_105b | <a href="#">integer</a> Response for when the fifth prescription medication was last taken (1-6).       |
| mhr_106b | <a href="#">integer</a> Response for when the sixth prescription medication was last taken (1-6).       |
| mhr_107b | <a href="#">integer</a> Response for when the seventh prescription medication was last taken (1-6).     |
| mhr_108b | <a href="#">integer</a> Response for when the eighth prescription medication was last taken (1-6).      |
| mhr_109b | <a href="#">integer</a> Response for when the ninth prescription medication was last taken (1-6).       |
| mhr_110b | <a href="#">integer</a> Response for when the tenth prescription medication was last taken (1-6).       |
| mhr_111b | <a href="#">integer</a> Response for when the eleventh prescription medication was last taken (1-6).    |
| mhr_112b | <a href="#">integer</a> Response for when the twelfth prescription medication was last taken (1-6).     |
| mhr_113b | <a href="#">integer</a> Response for when the thirteenth prescription medication was last taken (1-6).  |
| mhr_114b | <a href="#">integer</a> Response for when the fourteenth prescription medication was last taken (1-6).  |
| mhr_115b | <a href="#">integer</a> Response for when the fifteenth prescription medication was last taken (1-6).   |
| mhr_201b | <a href="#">integer</a> Response for when the first over-the-counter medication was last taken (1-6).   |
| mhr_202b | <a href="#">integer</a> Response for when the second over-the-counter medication was last taken (1-6).  |
| mhr_203b | <a href="#">integer</a> Response for when the third over-the-counter medication was last taken (1-6).   |
| mhr_204b | <a href="#">integer</a> Response for when the fourth over-the-counter medication was last taken (1-6).  |
| mhr_205b | <a href="#">integer</a> Response for when the fifth over-the-counter medication was last taken (1-6).   |
| mhr_206b | <a href="#">integer</a> Response for when the sixth over-the-counter medication was last taken (1-6).   |
| mhr_207b | <a href="#">integer</a> Response for when the seventh over-the-counter medication was last taken (1-6). |
| mhr_208b | <a href="#">integer</a> Response for when the eighth over-the-counter medication was last taken (1-6).  |
| mhr_209b | <a href="#">integer</a> Response for when the ninth over-the-counter medication was last taken (1-6).   |
| mhr_210b | <a href="#">integer</a> Response for when the tenth over-the-counter medication was last taken (1-6).   |

|          |                                                                                                   |
|----------|---------------------------------------------------------------------------------------------------|
| mhr_211b | <b>integer</b> Response for when the eleventh over-the-counter medication was last taken (1-6).   |
| mhr_212b | <b>integer</b> Response for when the twelfth over-the-counter medication was last taken (1-6).    |
| mhr_213b | <b>integer</b> Response for when the thirteenth over-the-counter medication was last taken (1-6). |
| mhr_214b | <b>integer</b> Response for when the fourteenth over-the-counter medication was last taken (1-6). |
| mhr_215b | <b>integer</b> Response for when the fifteenth over-the-counter medication was last taken (1-6).  |
| mhr_131b | <b>integer</b> Response for when the first new prescription medication was last taken (1-6).      |
| mhr_132b | <b>integer</b> Response for when the second new prescription medication was last taken (1-6).     |
| mhr_133b | <b>integer</b> Response for when the third new prescription medication was last taken (1-6).      |
| mhr_134b | <b>integer</b> Response for when the fourth new prescription medication was last taken (1-6).     |
| mhr_135b | <b>integer</b> Response for when the fifth new prescription medication was last taken (1-6).      |
| mhr_231b | <b>integer</b> Response for when the first new over-the-counter medication was last taken (1-6).  |
| mhr_232b | <b>integer</b> Response for when the second new over-the-counter medication was last taken (1-6). |
| mhr_233b | <b>integer</b> Response for when the third new over-the-counter medication was last taken (1-6).  |
| mhr_234b | <b>integer</b> Response for when the fourth new over-the-counter medication was last taken (1-6). |
| mhr_235b | <b>integer</b> Response for when the fifth new over-the-counter medication was last taken (1-6).  |

### Details

The function identifies NSAIDs based on ATC codes starting with "M01A". It checks all medication variables provided in the input data frame.

**\*\*Missing Data Codes:\*\***

- The function handles tagged NAs from the ``is_nsaid`` function and propagates them.

### Value

**numeric** Returns 1 if the person is taking any NSAIDs, 0 otherwise. If all medication information is missing, it returns a tagged NA.

**See Also**

is\_nsaid

**Examples**

```
This is a wrapper function and is not intended to be called directly by the user.
See `is_nsaid` for usage examples.
```

---

is\_other\_antihtn\_med *Other anti-hypertensive medications*

---

**Description**

This function checks if a given medication is another anti-hypertensive drug. This function processes multiple inputs efficiently.

**Usage**

```
is_other_antihtn_med(meucatc, npi_25b)
```

**Arguments**

meucatc            **character** ATC code of the medication.  
npi\_25b            **integer** Time when the medication was last taken.

**Details**

Identifies other anti-hypertensive drugs based on ATC codes starting with "C02", excluding a specific sub-code.

```
Missing Data Codes:
- `meucatc`: `9999996` (Not applicable), `9999997-9999999` (Missing)
- `npi_25b`: `6` (Not applicable), `7-9` (Missing)
```

**Value**

**numeric** 1 if medication is another anti-hypertensive drug, 0 otherwise. If inputs are invalid or out of bounds, the function returns a tagged NA.

**Examples**

```
Scalar usage: Single respondent
is_other_antihtn_med("C02AC04", 3)
Returns: 1

Example: Respondent has non-response values for all inputs.
result <- is_other_antihtn_med("9999998", 8)
result # Shows: NA
```

```

haven::is_tagged_na(result, "b") # Shows: TRUE (confirms it's tagged NA(b))
format(result, tag = TRUE) # Shows: "NA(b)" (displays the tag)

Multiple respondents
is_other_antihtn_med(c("C02AC04", "C02KX01"), c(3, 2))
Returns: c(1, 0)

Database usage: Applied to survey datasets
library(dplyr)
cycle3_meds |>
 mutate(other_antihtn = is_other_antihtn_med(meucatc, npi_25b)) |>
 head()

```

---

|                   |                                                                           |
|-------------------|---------------------------------------------------------------------------|
| recode_after_meds | <i>Recode variables that depend on derived medication variable inputs</i> |
|-------------------|---------------------------------------------------------------------------|

---

## Description

Wraps `recodeflow::rec_with_table()` for use after derived medication variables (e.g., `any_htn_med`, `diab_med`) have been recoded and merged into the main cycle dataset. Use this instead of `rec_with_table()` when deriving variables whose inputs include derived medication variables: it automatically excludes medication-specific rows from `variable_details` so that pre-computed medication columns are passed through via the copy entries rather than re-derived from raw ATC/MHR columns.

## Usage

```

recode_after_meds(
 data,
 variables,
 by = "clinicid",
 database_name = NULL,
 variable_details = chmsflow::variable_details
)

```

## Arguments

|                               |                                                                                                                     |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------|
| <code>data</code>             | <b>data.frame</b> Main cycle data with derived medication variables already merged.                                 |
| <code>variables</code>        | <b>character</b> Variable names to recode.                                                                          |
| <code>by</code>               | <b>character</b> Respondent identifier column. Default is "clinicid".                                               |
| <code>database_name</code>    | <b>character</b> Name of the database in <code>variable_details</code> . Defaults to the name of the data argument. |
| <code>variable_details</code> | <b>data.frame</b> Variable details table. Defaults to <code>chmsflow::variable_details</code> .                     |

## Value

**data.frame** Recoded data frame returned by `recodeflow::rec_with_table()`.

**See Also**

[recode\\_meds\\_cycles3to6\(\)](#), [recode\\_meds\\_cycles1to2\(\)](#)

**Examples**

```
cycle3 <- recode_meds_cycles3to6(cycle3, cycle3_meds, c("any_htn_med", "diab_med"))
cycle3_diab <- recode_after_meds(
 cycle3,
 c("lab_hba1", "diab_a1c", "diab_med", "ccc_51", "diab_status")
)
head(cycle3_diab[, c("clinicid", "diab_status")])
```

---

recode\_meds\_cycles1to2

*Recode medication variables for cycles 1-2 (wide format)*

---

**Description**

Recodes medication variables from cycles 1-2 wide-format data (one row per respondent, up to 80 ATC/MHR columns), and merges into the main cycle dataset. Wraps `recodeflow::rec_with_table()` and converts factor outputs to numeric.

**Usage**

```
recode_meds_cycles1to2(
 data,
 meds_data,
 variables,
 by = "clinicid",
 meds_database_name = NULL,
 variable_details = chmsflow::variable_details
)
```

**Arguments**

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>data</code>      | <a href="#">data.frame</a> Main cycle data to merge medication variables into.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <code>meds_data</code> | <a href="#">data.frame</a> Wide-format medication data (cycles 1-2). Must contain <code>clinicid</code> , ATC code columns <code>atc_101a-atc_115a</code> , <code>atc_131a-atc_135a</code> , <code>atc_201a-atc_215a</code> , <code>atc_231a-atc_235a</code> , and matching time-last-taken columns <code>mhr_101b-mhr_115b</code> , <code>mhr_131b-mhr_135b</code> , <code>mhr_201b-mhr_215b</code> , <code>mhr_231b-mhr_235b</code> . Column names are normalized to lowercase before recoding, so uppercase variants (e.g., <code>CLINICID</code> , <code>ATC_101A</code> ) are accepted. |
| <code>variables</code> | <a href="#">character</a> Medication variable names to derive (e.g., <code>"any_htn_med"</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <code>by</code>        | <a href="#">character</a> Respondent identifier column. Default is <code>"clinicid"</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

meds\_database\_name  
     **character** Name of the meds database in variable\_details. Defaults to the name of the meds\_data argument. Override when passing a transformed object (e.g., head()).

variable\_details  
     **data.frame** Variable details table. Defaults to chmsflow::variable\_details.

### Value

**data.frame** data with derived medication variables merged in as numeric columns.

### See Also

[recode\\_meds\\_cycles3to6\(\)](#), [aggregate\\_meds\\_by\\_person\(\)](#)

### Examples

```
result <- recode_meds_cycles1to2(
 cycle1,
 cycle1_meds,
 c("any_htn_med", "diab_med")
)
head(result[, c("clinicid", "any_htn_med", "diab_med")])
```

---

recode\_meds\_cycles3to6

*Recode medication variables for cycles 3-6 (long format)*

---

### Description

Recodes medication variables from cycles 3-6 long-format data (one row per medication per respondent), aggregates to one row per respondent, and merges into the main cycle dataset. Wraps `recodeflow::rec_with_table()` and [aggregate\\_meds\\_by\\_person\(\)](#).

### Usage

```
recode_meds_cycles3to6(
 data,
 meds_data,
 variables,
 by = "clinicid",
 meds_database_name = NULL,
 variable_details = chmsflow::variable_details
)
```

**Arguments**

|                    |                                                                                                                                                                                                                              |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| data               | <a href="#">data.frame</a> Main cycle data to merge medication variables into.                                                                                                                                               |
| meds_data          | <a href="#">data.frame</a> Long-format medication data (cycles 3-6) with columns <code>clinicid</code> , <code>meucatc</code> , and <code>npi_25b</code> .                                                                   |
| variables          | <a href="#">character</a> Medication variable names to derive (e.g., <code>"any_htn_med"</code> ).                                                                                                                           |
| by                 | <a href="#">character</a> Respondent identifier column. Default is <code>"clinicid"</code> .                                                                                                                                 |
| meds_database_name | <a href="#">character</a> Name of the meds database in <code>variable_details</code> . Defaults to the name of the <code>meds_data</code> argument. Override when passing a transformed object (e.g., <code>head()</code> ). |
| variable_details   | <a href="#">data.frame</a> Variable details table. Defaults to <code>chmsflow::variable_details</code> .                                                                                                                     |

**Value**

[data.frame](#) data with derived medication variables merged in as numeric columns.

**See Also**

[recode\\_meds\\_cycles1to2\(\)](#), [aggregate\\_meds\\_by\\_person\(\)](#)

**Examples**

```
result <- recode_meds_cycles3to6(
 cycle3,
 cycle3_meds,
 c("any_htn_med", "diab_med")
)
head(result[, c("clinicid", "any_htn_med", "diab_med")])
```

---

variables

*variables.csv*

---

**Description**

This dataset lists all the variables that are present in `chmsflow`.

**Usage**

```
data(variables)
```

**Source**

See [https://big-life-lab.github.io/chmsflow/articles/variables\\_sheet.html](https://big-life-lab.github.io/chmsflow/articles/variables_sheet.html) for more details.

**Examples**

```
data(variables)
str(variables)
```

---

```
variable_details variable-details.csv
```

---

**Description**

This dataset provides details on how variables are recoded in chmsflow.

**Usage**

```
data(variable_details)
```

**Source**

See [https://big-life-lab.github.io/chmsflow/articles/variable\\_details.html](https://big-life-lab.github.io/chmsflow/articles/variable_details.html) for more details.

**Examples**

```
data(variable_details)
str(variable_details)
```

# Index

## \* datasets

- cycle1, 29
  - cycle1\_meds, 29
  - cycle2, 30
  - cycle2\_meds, 30
  - cycle3, 31
  - cycle3\_meds, 31
  - cycle4, 32
  - cycle4\_meds, 32
  - cycle5, 33
  - cycle5\_meds, 33
  - cycle6, 34
  - cycle6\_meds, 34
  - variable\_details, 112
  - variables, 111
- adjust\_dbp, 3
- adjust\_dbp(), 5, 46
- adjust\_sbp, 4
- adjust\_sbp(), 4, 46
- aggregate\_meds\_by\_person, 5
- aggregate\_meds\_by\_person(), 110, 111
- calculate\_exercise\_daily\_avg, 6
- calculate\_exercise\_daily\_avg(), 9
- calculate\_exercise\_weekly, 8
- calculate\_exercise\_weekly(), 8, 25
- calculate\_fv\_daily\_cycles1to2, 9
- calculate\_fv\_daily\_cycles1to2(), 13, 24
- calculate\_fv\_daily\_cycles3to6, 11
- calculate\_fv\_daily\_cycles3to6(), 11, 24
- calculate\_gfr, 14
- calculate\_gfr(), 22, 43
- calculate\_household\_income, 15
- calculate\_household\_income(), 27
- calculate\_nonhdl, 17
- calculate\_nonhdl(), 28
- calculate\_pack\_years, 18
- calculate\_waist\_height\_ratio, 20
- categorize\_ckd, 22
- categorize\_ckd(), 15
- categorize\_diet\_quality, 23
- categorize\_diet\_quality(), 11, 13
- categorize\_exercise, 25
- categorize\_exercise(), 8, 9
- categorize\_income\_quintile, 26
- categorize\_income\_quintile(), 16, 94
- categorize\_nonhdl, 27
- categorize\_nonhdl(), 17
- character, 6, 55, 57, 58, 61, 64, 65, 69, 70, 73, 74, 77, 78, 81, 84, 85, 87, 90, 91, 97, 98, 101, 103, 104, 107–111
- cycle1, 29
- cycle1\_meds, 29
- cycle2, 30
- cycle2\_meds, 30
- cycle3, 31
- cycle3\_meds, 31
- cycle4, 32
- cycle4\_meds, 32
- cycle5, 33
- cycle5\_meds, 33
- cycle6, 34
- cycle6\_meds, 34
- data.frame, 6, 108–111
- derive\_alcohol\_risk, 35
- derive\_alcohol\_risk(), 38
- derive\_alcohol\_risk\_detailed, 37
- derive\_alcohol\_risk\_detailed(), 36
- derive\_cvd\_family\_history, 39
- derive\_cvd\_family\_history(), 42
- derive\_cvd\_personal\_history, 41
- derive\_cvd\_personal\_history(), 40
- derive\_diabetes\_status, 42
- derive\_hypertension, 44
- derive\_hypertension(), 4, 5, 43, 48
- derive\_hypertension\_adj, 47
- derive\_hypertension\_adj(), 46
- derive\_hypertension\_control, 49

`derive_hypertension_control()`, 54  
`derive_hypertension_control_adj`, 52  
`derive_hypertension_control_adj()`, 51

`integer`, 14, 16, 19, 22, 24, 25, 27, 28, 35–38, 40–43, 45–48, 50–53, 55, 58–61, 65–67, 70–74, 78–81, 85–87, 91–94, 98–101, 104–107

`is_ace_inhibitor`, 54  
`is_ace_med_cycles1to2`, 55  
`is_any_antihtn_med`, 61  
`is_any_htn_med_cycles1to2`, 62  
`is_bb_med_cycles1to2`, 67  
`is_beta_blocker`, 73  
`is_calcium_channel_blocker`, 74  
`is_ccb_med_cycles1to2`, 75  
`is_diab_med_cycles1to2`, 82  
`is_diabetes_med`, 81  
`is_diur_med_cycles1to2`, 88  
`is_diuretic`, 87  
`is_lowest_income_quintile`, 94  
`is_lowest_income_quintile()`, 16, 27  
`is_misc_htn_med_cycles1to2`, 95  
`is_nsaid`, 100  
`is_nsaid_med_cycles1to2`, 101  
`is_other_antihtn_med`, 107

`numeric`, 3–5, 7, 9–17, 19, 21–23, 25, 26, 28, 40, 55, 60, 61, 67, 72–74, 80, 81, 87, 88, 93, 100, 101, 106, 107

`recode_after_meds`, 108  
`recode_meds_cycles1to2`, 109  
`recode_meds_cycles1to2()`, 6, 109, 111  
`recode_meds_cycles3to6`, 110  
`recode_meds_cycles3to6()`, 6, 109, 110

`variable_details`, 112  
`variables`, 111